



DEPARTMENT OF HEALTH CARE ACCESS AND INFORMATION
OFFICE OF STATEWIDE HOSPITAL PLANNING AND DEVELOPMENT

APPLICATION FOR HCAI PREAPPROVAL OF
MANUFACTURER'S CERTIFICATION (OPM)

OFFICE USE ONLY

APPLICATION #: OPM-0652

HCAI Preapproval of Manufacturer's Certification (OPM)

Type: New Renewal/Update

Manufacturer Information

Manufacturer: Abbott Diagnostics Division

Manufacturer's Technical Representative: Claudia Moreno

Mailing Address: 1921 Hurd Drive, MS 2-33, Irving, TX 75038

Telephone: (972) 518-7691

Email: Claudia.Moreno@abbott.com

Product Information

Product Name: Abbott Automation Solutions - Archive II, Spiral Element & Elevated Tracks

Product Type: Automated Pre/Post Analytical Processing Laboratory Instruments

Product Model Number: Archive II Single, Archive II Twin, Archive II Loader Module, Archive II Storage, Spiral Element, Elevated Tracks: 20, 40 & 80 cm Straight Sections, 90 Degree Turn Section, 3 & 4 Way Roundabout; Floor Supported Tracks: 20, 40 and 80cm Straight Sections.

General Description: The Abbott Automated Solutions is a Modular System designed to automate pre-analytical and post-analytical processing, sample-handling, and processing in the Laboratory. System consolidates multiple analytical instruments into a unified work station by employing a common sample processing capability.

Applicant Information

Applicant Company Name: CYS Structural Engineers, Inc.

Contact Person: Dieter Siebald

Mailing Address: 2495 Natomas Park Drive, #650, Sacramento, CA 95833

Telephone: (916) 920-2020

Email: dieters@cyseng.com

Title: Structural Engineer

"A healthier California where all receive equitable, affordable, and quality health care"

STATE OF CALIFORNIA – HEALTH AND HUMAN SERVICES AGENCY





**DEPARTMENT OF HEALTH CARE ACCESS AND INFORMATION
OFFICE OF STATEWIDE HOSPITAL PLANNING AND DEVELOPMENT**

Registered Design Professional Preparing Engineering Recommendations

Company Name: CYS STRUCTURAL ENGINEERS, INC.

Name: Dieter Siebald California License Number: S4346

Mailing Address: 2495 Natomas Park Drive, Suite 650, Sacramento, CA 95833

Telephone: (916) 920-2020 Email: dieters@cyseng.com

HCAI Special Seismic Certification Preapproval (OSP)

Special Seismic Certification is preapproved under OSP OSP Number: _____

Certification Method

Testing in accordance with: ICC-ES AC156 FM 1950-16

Other(s) (Please Specify): _____

*Use of criteria other than those adopted by the California Building Standards Code, 2022 (CBSC 2022) for component supports and attachments are not permitted. For distribution system, interior partition wall, and suspended ceiling seismic bracings, test criteria other than those adopted in the CBSC 2022 may be used when approved by HCAI prior to testing.

Analysis

Experience Data

Combination of Testing, Analysis, and/or Experience Data (Please Specify): _____

HCAI Approval

Date: 7/23/2024

Name: William Staehlin Title: Senior Structural Engineer

Condition of Approval (if applicable): _____

"A healthier California where all receive equitable, affordable, and quality health care"

STATE OF CALIFORNIA – HEALTH AND HUMAN SERVICES AGENCY




OPM-0652
TABLE OF CONTENTS

	PAGE
GENERAL INFORMATION	
GENERAL NOTES	101-102.1
DESIGN CRITERIA & ABBREVIATIONS	103
COMPONENTS	
COMPONENT SCHEDULE	201
COMPONENT CONFIGURATIONS	202
ARCHIVE II: COMPONENTS	210.01-210.02C
SPIRAL ELEMENT & ELEVATED TRACKS: COMPONENTS	210.03-210.08
FLOOR SUPPORTED TRACKS: COMPONENTS 9-11	210.09-210.11
FLOOR MOUNTED TRACK DETAILS	220-221
SEISMIC BRACKET DETAILS	
SEISMIC BRACKET 1	301
SEISMIC BRACKET 2	302
SEISMIC BRACKET 3	303
SEISMIC BRACKET 4	304
HAT BRACKET	
TRACK TO COMPONENT CONNECTIONS	310 320-322
FLOOR MOUNTED ATTACHMENT	
CASE 1 - TYPICAL STRUT DETAILS	401-402
CASE 1 & 2 - SEISMIC BRACKETS 1, 2 & 3	403
CASE 1 & 2 - SEISMIC HAT BRACKET	404
ELEVATED TRACK ATTACHMENT	
BRACE PERPENDICULAR TO DECK	501
BRACE PARALLEL TO DECK	502
BRACE TO CONCRETE FLOOR	503

NOTES:

THESE DRAWINGS ARE PREPARED FOR ABBOTT LABORATORIES, AN ILLINOIS CORPORATION, ABBOTT PARK, ILLINOIS.

1. THE CONTRACTOR SHALL OBTAIN A COPY OF THIS PRE-APPROVAL FROM THE HCAI PRE-APPROVAL PROGRAM WEBSITE AND PROVIDE ONE COPY FOR THE INSPECTOR OF RECORD.
2. THIS PRE-APPROVAL COVERS THE SUPPORTS AND ATTACHMENTS OF THE LABORATORY EQUIPMENT TO THE STRUCTURE.
3. BRACKETS, STRUT PLATES & CONCRETE ANCHORS SHALL BE PROVIDED & INSTALLED BY THE CONTRACTOR.



NOT SEOR

SHEET TITLE: TABLE OF CONTENTS					
ABBOTT AUTOMATION SOLUTIONS ARCHIVE II, SPIRAL ELEMENT & ELEVATED TRACKS SUPPORTS & ATTACHMENTS	CYS STRUCTURAL ENGINEERS, INC. 2710 GATEWAY OAKS DRIVE, SUITE 190N SACRAMENTO, CA 95833	TEL (916) 920-2020 www.cyseng.com	Rev Description Date	Job No: 20097.005 Date: 07/11/2024 By: CYS Page: 101	

L:\Jobs\20097\20097 - AA System OPM\OPM 2\ACAD\STRU\SI_20097-05.dwg Time: Jul 11, 2024 - 03:17pm LogIn: camachom DimScale: 1 LTScale: 6

GENERAL NOTES:

1. THIS CALIFORNIA DEPARTMENT OF HEALTH CARE ACCESS & INFORMATION (HCAI) OFFICE OF STATEWIDE HOSPITAL PLANNING & DEVELOPMENT (OSHPD) PRE-APPROVAL OF MANUFACTURER'S CERTIFICATION (OPM) IS BASED ON THE CBC 2022. THE DEMAND (DESIGN FORCES) FOR USE W/ THIS OPM SHALL BE BASED ON THE CBC 2022.
2. IT IS THE RESPONSIBILITY OF THE STRUCTURAL ENGINEER OF RECORD FOR A SITE SPECIFIC PROJECT TO VERIFY:
 - A. THE ADEQUACY OF THE NEW OR (E) STRUCTURE TO RESIST THE FORCES & WT SPECIFIED FOR EACH EQUIP IN ADDITION TO ALL OTHER LOADS. PROVIDE & DESIGN SUPPLEMENTARY MEMBERS AS REQ.
 - B. THAT THE FLR ANCHORS ARE LOCATED AT AN ADEQUATE DISTANCE FROM ANY SLAB EDGES OR OPENINGS.
 - C. THAT THE FLR ANCHORS ARE LOCATED AT AN ADEQUATE DISTANCE FROM ANY NEW OR (E) ANCHORS. THE SPACING SHOWN IN THE TEST LOADS IN TABLES 1.1 & 1.2 ON THIS PG IS THE REQ MIN SPACING OF THE GIVEN DIA ANCHORS. THE REQ SPACING FROM ANCHORS OF OTHER DIA & EMBEDMENTS MAY VARY & SHALL BE EVALUATED BY THE SEOR.
 - D. THAT THE INSTALLATION IS IN CONFORMANCE W/ THE CBC 2022 & W/ THE DTLS SHOWN IN THIS PRE-APPROVAL.
 - E. THAT THE ACTUAL EQUIP'S WT, CENTER OF GRAVITY (CG) LOCATION, ANCHOR LOCATIONS, ANCHOR DTLS, & THE MATERIAL & GA OF THE EQUIP WHERE ATTACHMENTS ARE MADE, AGREE W/ THE INFORMATION SHOWN ON THE PRE-APPROVAL DOCUMENTS.
 - F. THAT THE CONC SLAB TO WHICH THE EQUIP IS ANCHORED SHALL MEET THE REQUIREMENTS OF THE APPLICABLE ICC REPORT & THIS OPM.
- 3.1. BRACKETS 1 & 3 EXPANSION ANCHORS INSTALLED IN NWC OR SLWC SHALL BE CARBON STL HILTI KB-TZ2 EXPANSION ANCHORS COMPLYING W/ ESR-4266 REISSUED DECEMBER 2021.
 - A. INSTALLATION: INSTALL THE EXPANSION ANCHORS IN ACCORDANCE W/ THE REQUIREMENTS GIVEN IN THE ICC EVALUATION REPORT FOR THE SPECIFIC ANCHOR & THE PARAMETERS GIVEN IN THE TABLE ON THIS PG. PROVIDE FULL THRD ENGAGEMENT FOR NUT & WASHER.
 - B. JOB TESTING: FOR VERIFYING SATISFACTORY INSTALLATION WORKMANSHIP, PERFORM JOB SITE TESTING IN ACCORDANCE W/ THE TEST LOAD TABLE PROVIDED IN THIS DOCUMENT. TORQUE 50% OF THE INSTALLED ANCHORS. ALL TESTS SHALL BE CONDUCTED IN THE PRESENCE OF THE SPECIAL INSPECTOR & REPORT OF TEST RESULTS SHALL BE SUBMITTED TO THE INSPECTOR OF RECORD, OWNER & ARCHITECT OR ENGINEER IN RESPONSIBLE CHARGE. IF ANY ANCHOR FAILS THE TEST, TEST ALL ANCHORS. THE TEST SHALL BE PERFORMED 24 HOURS OR MORE AFTER INSTALLATION. TESTING MAY BE DONE PRIOR TO EQUIP INSTALLATION, HOWEVER, THE NUT SHALL BE RETORQUED TO INSTALLATION TORQUE AFTER EQUIP INSTALL. ALSO, REFER TO 2022 CBC 1910A.5 "TESTS FOR POST-INSTALLED ANCHORS IN CONCRETE".
 - C. FAILURE/ACCEPTANCE CRITERIA: THE FOLLOWING CRITERIA APPLIES FOR THE ACCEPTANCE OF INSTALLED ANCHORS:
 - **TORQUE WRENCH METHOD:** THE APPLICABLE TEST TORQUE MUST BE REACHED W/IN THE FOLLOWING LIMITS: WEDGE TYPE: ONE-HALF (1/2) TURN OF THE NUT.
 - D. AVOID DAMAGING (E) STL REINF IN CONC SLAB WHEN INSTALLING CONC EXPANSION ANCHORS.
 - E. TEST VALUES: APPLY TEST LOADS TO ANCHORS WITHOUT REMOVING THE NUT IF POSSIBLE. FOR CASE 2, SEE TABLE 1.1 BELOW.

- 3.2 BRACKET 2 EXPANSION ANCHORS INSTALLED IN NWC OR SLWC SHALL BE CARBON STL HILTI HSL4 EXPANSION ANCHORS COMPLYING W/ ESR-4386 REVISED AUGUST 2023.
 - A. INSTALLATION: INSTALL THE EXPANSION ANCHORS IN ACCORDANCE W/ THE REQUIREMENTS GIVEN IN THE ICC EVALUATION REPORT FOR THE SPECIFIC ANCHOR & THE PARAMETERS GIVEN IN THE TABLE ON THIS PG. PROVIDE FULL THRD ENGAGEMENT FOR NUT & WASHER.
 - B. JOB TESTING: FOR VERIFYING SATISFACTORY INSTALLATION WORKMANSHIP, PERFORM JOB SITE TESTING IN ACCORDANCE W/ THE TEST LOAD TABLE PROVIDED IN THIS DOCUMENT. TORQUE 50% OF THE INSTALLED ANCHORS. ALL TESTS SHALL BE CONDUCTED IN THE PRESENCE OF THE SPECIAL INSPECTOR & REPORT OF TEST RESULTS SHALL BE SUBMITTED TO THE INSPECTOR OF RECORD, OWNER & ARCHITECT OR ENGINEER IN RESPONSIBLE CHARGE. IF ANY ANCHOR FAILS THE TEST, TEST ALL ANCHORS. THE TEST SHALL BE PERFORMED 24 HOURS OR MORE AFTER INSTALLATION. TESTING MAY BE DONE PRIOR TO EQUIP INSTALLATION, HOWEVER, THE NUT SHALL BE RETORQUED TO INSTALLATION TORQUE AFTER EQUIP INSTALL. ALSO, REFER TO 2022 CBC 1910A.5 "TESTS FOR POST-INSTALLED ANCHORS IN CONCRETE".
 - C. FAILURE/ACCEPTANCE CRITERIA: THE FOLLOWING CRITERIA APPLIES FOR THE ACCEPTANCE OF INSTALLED ANCHORS:
 - **TORQUE WRENCH METHOD:** THE APPLICABLE TEST TORQUE MUST BE REACHED W/IN THE FOLLOWING LIMITS: WEDGE TYPE: ONE-QUARTER (1/4) TURN OF THE NUT.
 - D. AVOID DAMAGING (E) STL REINF IN CONC SLAB WHEN INSTALLING CONC EXPANSION ANCHORS.
 - E. TEST VALUES: APPLY TEST LOADS TO ANCHORS WITHOUT REMOVING THE NUT IF POSSIBLE. FOR CASE 2, SEE TABLE 1.2 BELOW.

TABLE 1.2

CONDITION OF ANCHORAGE	ANCHOR OUTSIDE DIA (mm) da	NOMINAL ANCHOR DIA	EFFECTIVE EMBED (mm) hef	HOLE DEPTH (mm) ho	MIN CONC THICKNESS (INCH) h _{min}	MIN CONC EDGE DISTANCE (INCH)	MIN AB SPACING (INCH)	TEST LOAD TORQUE (Nm)
CASE 2	18	M12	80	105	5 3/8	12	4	60





TABLE 1.1

CONDITION OF ANCHORAGE	ANCHOR DIA (INCH) da	INSTALLATION EMBED (INCH) h _{nom}	EFFECTIVE EMBED (INCH) hef	HOLE DEPTH (INCH) ho	MIN CONC THICKNESS (INCH) h _{min}	MIN CONC EDGE DISTANCE (INCH)	MIN AB SPACING (INCH)	TEST LOAD TORQUE (FT-LBS)
CASE 2	1/2	2 1/2	2	2 3/4	4	12	5 1/2	50



NOT SEOR

SHEET TITLE: GENERAL NOTES

Rev	Description	Date	Job No:
			20097.005
			Date: 07/11/2024
			By: CYS
			Page: 102



ABBOTT AUTOMATION SOLUTIONS
ARCHIVE II, SPIRAL ELEMENT & ELEVATED TRACKS
SUPPORTS & ATTACHMENTS



CYS STRUCTURAL ENGINEERS, INC.
2710 GATEWAY OAKS DRIVE, SUITE 190N
SACRAMENTO, CA 95833
TEL (916) 920-2020
www.cyseng.com

C:\Users\comachom\appdata\local\temp\AcPublish_61412\S1_20097-05.dwg Time:Jul08,2024-03:43pm Login:comachom Dimscale:1 LScale:6

GENERAL NOTES: (CONTINUED)


4. BOLTS THROUGH CONC ON MTL DECK:
 - A. BOLTS SHALL BE TORQUED BY $\frac{3}{4}$ TURN OF THE NUT AFTER SNUG TIGHT CONDITION IS ACHIEVED, UNO. THE SNUG TIGHT CONDITION IS DEFINED AS THE TIGHTNESS REQ TO BRING THE CONNECTED PLIES INTO FIRM CONTACT.
 - B. THRU-BOLT HOLES SHALL BE $\frac{1}{16}$ " LARGER THAN BOLT SIZE (HOLE SIZE = BOLT SIZE + $\frac{1}{16}$ ")
 - C. THRU-BOLTS IN CONC SHALL RECEIVE SPECIAL INSPECTION & TESTING IN ACCORDANCE W/ REQUIREMENTS FOR POST-INSTALLED ANCHORS. THRU-BOLTS W/ STL TO STL CONNECTION IN TENSION DO NOT REQUIRE TESTING.
5. EXPANSION ANCHORS TO BOTT OF CONC FILL OVER MTL DECK:
 - A. HILTI KB-TZ2 (ICC ESR-4266) TENSION TEST LOAD. FOR CASE 1, SEE TABLE 2 BELOW.

TABLE 2

CONDITION OF ANCHORAGE	ANCHOR DIA (INCH) d_a	INSTALLATION EMBED (INCH) h_{nom}	EFFECTIVE EMBED (INCH) h_{ef}	HOLE DEPTH (INCH) h_o	MIN CONC THICKNESS (INCH) h_{min}	MIN CONC EDGE DISTANCE (INCH)	MIN AB SPACING (INCH)	MAX INSTALLATION TORQUE (FT-LBS)
CASE 1	$\frac{1}{4}$	$1\frac{3}{4}$	$1\frac{1}{2}$	2	$3\frac{3}{4}$	1*	10*	4

* SEE PG 401 IN THIS OPM & FIGURE 5B IN ESR-4266


6. TWO (2) CASES OF ATTACHMENT ARE SPECIFIED & PRESENTED IN THIS PRE-APPROVAL:



CASE 1: ATTACHMENT DETAILS LOCATED AT UPPER FLRS ABV THE BASE OF A BLDG ($z/h \leq$ PER COMPONENT SCHED ON PG 201). THE FLRS ARE ASSUMED TO BE BUILT OF A MIN $3\frac{3}{4}$ " SLWC TOPPING OVER 3" DEEP MIN 20 GA MTL DECK ($f'_c = 3000$ PSI, MIN). ANCHORS SHALL BE A325 STL THRD ROD THRU CONC FILL & MTL DECK.

CASE 2: ATTACHMENT DETAILS LOCATED AT OR BLW THE BASE OF A BLDG ($z/h=0$). THE FLRS ARE ASSUMED TO BE BUILT OF A MIN 4" NWC SLAB FOR BRACKETS 1 & 3 & A MIN $5\frac{3}{8}$ " NWC SLAB FOR BRACKET 2. ($f'_c = 3000$ PSI, MIN).

7. THIS PRE-APPROVAL MAY BE USED AT ANY GEOGRAPHICAL LOCATION IN THE STATE OF CALIFORNIA WHERE S_{ps} IS LESS THAN OR EQUAL TO VALUES PUBLISHED IN COMPONENT SCHED ON PG 201.



NOT SEOR

SHEET TITLE: GENERAL NOTES (CONTINUED)				Rev	Description	Date	Job No: 20097.005	
ABBOTT AUTOMATION SOLUTIONS ARCHIVE II, SPIRAL ELEMENT & ELEVATED TRACKS SUPPORTS & ATTACHMENTS				CYS STRUCTURAL ENGINEERS, INC. 2710 GATEWAY OAKS DRIVE, SUITE 190N TEL (916) 920-2020 SACRAMENTO, CA 95833 www.cyseng.com				Date: 07/11/2024
								By: CYS
								Page: 102.1

c:\Users\comachom\appdata\local\temp\AcPublish_80540\S1_20097-05.dwg Time: May 13, 2024 - 11:06am Login: comachom DimScale: 1 LTScale: 6

DESIGN CRITERIA

SUPPORT & ATTACHMENT DESIGN IS PER 2022 CBC AT LRFD LEVEL FORCES.

FLOOR MOUNTED EQUIPMENT:

OTHER MECHANICAL OR ELECTRICAL COMPONENTS PER TABLE 13.6-1 OF ASCE 7-16 INCLUDING SUPPLEMENT #1 & ERRATA:

$a_p = 1.0 \quad R_p = 1.5 \quad I_p = 1.5 \quad \Omega_0 = 1.5$ (CONC ANCHORS)

W_p AS NOTED ON COMPONENT SCHEDULE ON PG 201

FOR CASE 1 – UPPER FLRS ABV THE BASE, $z/h \leq$ VALUES PER COMPONENT SCHEDULE OF PG 201

S_{DS} = PER COMPONENT SCHEDULE OF PG 201

FOR CASE 2 – SLAB AT OR BLW BASE, $z/h = 0$

S_{DS} = PER COMPONENT SCHEDULE OF PG 201

ELEVATED TRACKS:

DISTRIBUTION SYSTEM: ELECTRICAL CONDUIT & CABLE TRAYS.

$a_p = 2.5 \quad R_p = 6 \quad I_p = 1.5 \quad \Omega_0 = 1.5$ (CONC ANCHORS)

W_p = AS NOTED ON COMPONENT SCHED ON PG 201

FOR CASE 1 – UPPER FLRS ABV THE BASE, $z/h \leq$ VALUES PER COMPONENT SCHEDULE OF PG 201

S_{DS} = PER COMPONENT SCHEDULE OF PG 201

LOAD COMBINATIONS

$(0.9 - 0.2 S_{DS}) D - \Omega_0 F_p$ (FOR MAX TENSION)

$(1.2 + 0.2 S_{DS}) D + \Omega_0 F_p$ (FOR MAX COMPRESSION)

DESIGN PARAMETERS & BRACING GUIDELINES – ELEVATED TRACKS

- DESIGN & INSTALLATION OF THE SEISMIC BRG FOR THE ELEVATED TRACK SYSTEMS MUST CONFORM TO ACSE/SEI 7-16 SECTION 13 & 2022 CBC SECTION 1617A.1.24.
- THE SPACING & DETAILS OF THE SUPPORT & BRG OF ELEVATED TRACK SYSTEMS MUST COMPLY W/ ASCE/SEI 7-16 SECTION 13.6 AND 2022 CBC SECTIONS 1601A.1.4 & 1617A.1.17 APPLICABLE ONLY TO HCAI 1,2,4,5 DESIGNATED PROJECTS.
- SEISMIC BRG MUST HAVE A MAX SPACING NOT EXCEEDING THAT SPECIFIED IN THESE DRAWINGS.
- SEISMIC BRACE ANCHORAGE MUST BE AT LEAST 6" AWAY FROM ANY OTHER ANCHORAGE OR CONC EDGES, UNO.

ABBREVIATIONS:

@	AT
ABV	ABOVE
ASME	AMERICAN SOCIETY OF MECHANICAL ENGINEERS
ASTM	AMERICAN SOCIETY FOR TESTING & MATERIALS
BLDG	BUILDING
BLW	BELOW
BRCG	BRACING
CBC	CALIFORNIA BUILDING CODE
CG	CENTER OF GRAVITY
CL	CENTERLINE
CONC	CONCRETE
COORD	COORDINATE
DBL	DOUBLE
DIA (ϕ)	DIAMETER
(E)	EXISTING CONDITION
ELEV	ELEVATION
EN	EDGE NAILING/EDGE FASTENING
EQUIP	EQUIPMENT
ES	EACH SIDE
f'_c	MINIMUM ULTIMATE COMPRESSIVE STRENGTH OF CONCRETE
FLR	FLOOR
FT (')	FOOT/FEET
F_y	SPECIFIED MINIMUM YIELD STRESS OF STEEL
GA	GAUGE
HCAI	DEPARTMENT OF HEALTH CARE ACCESS AND INFORMATION
IN (")	INCH
KSI	KIPS PER SQUARE INCH
LBS	POUNDS
LLH	LONG LEG HORIZONTAL
LLV	LONG LEG VERTICAL
LRFD	LOAD AND RESISTANCE FACTOR DESIGN
MAX	MAXIMUM
MFR	MANUFACTURER
MIN	MINIMUM
mm	MILLIMETER
MTL	METAL
NO. (#)	NUMBER OR POUNDS
NWC	NORMAL WEIGHT CONCRETE
OPP	OPPOSITE
PG	PAGE
P	PLATE
PSI	POUNDS PER SQUARE INCH
SCHED	SCHEDULE
SEOR	STRUCTURAL ENGINEER OF RECORD
SLWC	SAND-LIGHTWEIGHT CONCRETE
SS	STAINLESS STEEL
STD	STANDARD
STL	STEEL

Tu	ANCHORAGE TENSION REACTION DUE TO SEISMIC FORCE AT LRFD
THK	THICK/THICKNESS
THRD	THREAD OR THREADED
TYP	TYPICAL
Vu	ANCHORAGE SHEAR REACTION DUE TO SEISMIC FORCE AT LRFD
VERT	VERTICAL
W/	WITH
W_p	OPERATING WEIGHT
WT	WEIGHT

FRACTION & UNIT CONVERSIONS (FOR REFERENCE ONLY)

FRACTION	DECIMAL	mm	FRACTION	DECIMAL	mm
1/32	0.03	0.8	17/32	0.53	13.5
1/16	0.06	1.6	9/16	0.56	14.3
3/32	0.09	2.4	19/32	0.59	15.1
1/8	0.13	3.2	5/8	0.63	15.9
5/32	0.16	4.0	21/32	0.66	16.7
3/16	0.19	4.8	11/16	0.69	17.5
7/32	0.22	5.6	23/32	0.72	18.3
1/4	0.25	6.4	3/4	0.75	19.1
9/32	0.28	7.1	25/32	0.78	19.8
5/16	0.31	7.9	13/16	0.81	20.6
11/32	0.34	8.7	27/32	0.84	21.4
3/8	0.38	9.5	7/8	0.88	22.2
13/32	0.41	10.3	29/32	0.91	23.0
7/16	0.44	11.1	15/16	0.94	23.8
15/32	0.47	11.9	31/32	0.97	24.6
1/2	0.50	12.7			



NOT SEOR

SHEET TITLE: DESIGN CRITERIA & ABBREVIATIONS

Rev	Description	Date	Job No: 20097.005
			Date: 07/11/2024
			By: CYS
			Page: 103



ABBOTT AUTOMATION SOLUTIONS
ARCHIVE II, SPIRAL ELEMENT & ELEVATED TRACKS
SUPPORTS & ATTACHMENTS




CYS STRUCTURAL ENGINEERS, INC.
2710 GATEWAY OAKS DRIVE, SUITE 190N TEL (916) 920-2020
SACRAMENTO, CA 95833 www.cyseng.com

c:\Users\comachom\appdata\local\temp\AcPublish_80540\S1_20097-05.dwg Time: 07/23/2024 11:06am Login: comachom DimScale: 1 LTScale: 6

C:\Users\comachom\appdata\local\temp\AcPublish_80540\S1_20097-05.dwg Time:May 13, 2024 - 11:06am Login:comachom Dimscale:1 L1Scale:6



	PAGE NO.	COMPONENT	LEVELING FOOT DIMS		CG LOCATION			WEIGHT (W _p)	COMPONENT TYPE			ANCHOR R/ BRACKET REF	SEISMIC DESIGN VALUES								
			WIDTH	DEPTH	\bar{x}	\bar{y}	\bar{z}		FLR MOUNTED MODULE	FLR SUPPORTED TRACKS	ELEVATED TRACK		CASE 1		CASE 2						
													S _{ps}	z/h	S _{ps}						
ARCHIVE II	210.01	ARCHIVE II SINGLE	SEE PG 210.01					N/A	X			N/A	1.90	0.90	2.50						
	210.02	ARCHIVE II TWIN	SEE PG 210.02					N/A	X			N/A	1.90	0.90	2.50						
	210.02A	ARCHIVE II - LOADER MODULE	26.9"	22.8"	12.42"	16.29"	33.09"	587#	X			PGS 301-301B	1.90	0.90	2.50						
	210.02B	ARCHIVE II - STORAGE	52.8"	25.8"	27.01"	13.78"	36.61"	1778#	X			PG 302	1.1	0.90	1.9						
ELEVATED TRACK COMPONENTS	210.03	SPIRAL ELEMENT	SEE PG 210.03		17.98"	17.54"	50.29"	561#	X			PG 303	2.50	1.0	2.50						
	210.04	STRAIGHT SECTION- 20cm	N/A		5.45"	2.80"	3.48"	11#				SEE PGS 501-503	2.50	1.0	N/A						
	210.05	STRAIGHT SECTION- 40cm			9.71"	2.80"	3.54"	13#			X										
	210.06	STRAIGHT SECTION- 80cm			17.93"	2.80"	3.57"	26#			X										
	210.07	90 DEGREE TURN SECTION			4.88"	5.75"	3.53"	13#			X										
	210.08	ROUNDABOUT - 3-WAY			15.91"	15.91"	3.41"	66#			X										
	210.08	ROUNDABOUT - 4-WAY			15.91"	15.91"	3.41"	66#			X										
	FLR SUPPORTED TRACKS	210.09			STRAIGHT SECTION - 20cm	7.95"	6.69"	3.98"	3.35"	19.33"	26#						X		SEE PGS 220 & 310	2.50	1.0
210.10		STRAIGHT SECTION - 40cm			15.91"	6.69"	7.95"	3.35"	20.33"	50#						X					
210.11		STRAIGHT SECTION - 80cm	31.81"	6.69"	15.91"	3.35"	20.86"	83#		X											



NOT SEOR

SHEET TITLE: COMPONENT SCHEDULE				Rev	Description	Date	Job No: 20097.005
ABBOTT AUTOMATION SOLUTIONS ARCHIVE II, SPIRAL ELEMENT & ELEVATED TRACKS SUPPORTS & ATTACHMENTS				CYS STRUCTURAL ENGINEERS, INC. 2710 GATEWAY OAKS DRIVE, SUITE 190N SACRAMENTO, CA 95833 TEL (916) 920-2020 www.cyseng.com			Date: 07/11/2024
							By: CYS
							Page: 201

c:\Users\comachom\appdata\local\temp\AcPublish_80540\S1_20097-05.dwg Time:May 13, 2024 - 10:44am Login:comachom DimScale:1 LTScale:6



SHEET TITLE: COMPONENT CONFIGURATION



Rev	Description	Date	Job No:	20097.005
			Date:	07/11/2024
			By:	CYS
			Page:	202




ABBOTT AUTOMATION SOLUTIONS
 ARCHIVE II, SPIRAL ELEMENT & ELEVATED TRACKS
 SUPPORTS & ATTACHMENTS



CYS STRUCTURAL ENGINEERS, INC.
 2710 GATEWAY OAKS DRIVE, SUITE 190N
 SACRAMENTO, CA 95833
 TEL (916) 920-2020
 www.cyseng.com



NOTE: THE STORAGE COMPONENT MAY BE PLACED ON THE RIGHT OR LEFT SIDE OF THE LOADER MODULE





NOT SEOR


SHEET TITLE: MODULE: ARCHIVE II SINGLE BASE PLAN & ELEVATIONS ABBOTT AUTOMATION SOLUTIONS ARCHIVE II, SPIRAL ELEMENT & ELEVATED TRACKS SUPPORTS & ATTACHMENTS	CYS STRUCTURAL ENGINEERS, INC. 2710 GATEWAY OAKS DRIVE, SUITE 190N SACRAMENTO, CA 95833 TEL (916) 920-2020 www.cyseng.com	Rev	Description	Date	Job No: 20097.005
					Date: 07/11/2024
					By: CYS
					Page: 210.01

C:\Users\comachom\appdata\local\temp\AcPublish_61412\S1_20097-05.dwg Time: Jul 08, 2024 - 03:44pm Login: comachom Dimscale: 1 LScale: 6

c:\Users\comachom\appdata\local\temp\AcPublish_61412\51_20097-05.dwg Time:Jul08,2024-03:44pm Login:comachom Dimscale:1 LTScale:6



BASE PLAN VIEW
 DATE: 07/23/2024



NOT SEOR


SHEET TITLE: MODULE: ARCHIVE II TWIN
 BASE PLAN & ELEVATIONS

ABBOTT AUTOMATION SOLUTIONS
 ARCHIVE II, SPIRAL ELEMENT & ELEVATED TRACKS
 SUPPORTS & ATTACHMENTS


CYS STRUCTURAL ENGINEERS, INC.
 2710 GATEWAY OAKS DRIVE, SUITE 190N
 SACRAMENTO, CA 95833
 TEL (916) 920-2020
 www.cyseng.com

Rev	Description	Date	Job No:
			20097.005
			Date: 07/11/2024
			By: CYS
			Page: 210.02


c:\Users\comachom\appdata\local\temp\AcPublish_80540\1_20097-05.dwg Time:May 13, 2024 11:06am Login:comachom DimScale:1 LScale:6




**FRONT
BASE PLAN VIEW A-A**




FRONT ELEV



LEFT SIDE ELEV





DETAIL B-B



MAX ANCHOR FORCES AT LRFD AT LEVELING LEG

	T _{max}	C _{max}	V _{max}
CASE 1 ²	1182#	1571#	413#
CASE 2 ¹	698#	1087#	249#

1. INCLUDES OVERSTRENGTH FACTOR (Ω_o).
2. OVERSTRENGTH FACTOR (Ω_o) MUST BE APPLIED FOR ANCHORAGE TO CONC.



SHEET TITLE: MODULE: ARCHIVE II LOADER MODULE
BASE PLAN & ELEVATIONS



ABBOTT AUTOMATION SOLUTIONS
ARCHIVE II, SPIRAL ELEMENT & ELEVATED TRACKS
SUPPORTS & ATTACHMENTS




CYS STRUCTURAL ENGINEERS, INC.
2710 GATEWAY OAKS DRIVE, SUITE 190N
SACRAMENTO, CA 95833
TEL (916) 920-2020
www.cyseng.com

Rev	Description	Date	Job No:
			20097.005
			Date: 07/11/2024
			By: CYS
			Page: 210.02A


MAX ANCHOR FORCES AT LRFD AT LEVELING LEG

	T _{max}	C _{max}	V _{max}
CASE 1 ²	2440#	3416#	978#
CASE 2 ¹	1940#	2926#	776#



1. INCLUDES OVERSTRENGTH FACTOR (Ω_o).
2. OVERSTRENGTH FACTOR (Ω_o) MUST BE APPLIED FOR ANCHORAGE TO CONC.



FRONT




FRONT ELEV



BASE PLAN VIEW A-A

NOTE:
STORAGE RIGHT SHOWN.
STORAGE LEFT MIRRORED



NOT SEOR

SHEET TITLE: MODULE: ARCHIVE II STORAGE
BASE PLAN & ELEVATIONS


ABBOTT AUTOMATION SOLUTIONS
ARCHIVE II, SPIRAL ELEMENT & ELEVATED TRACKS
SUPPORTS & ATTACHMENTS

CYS STRUCTURAL ENGINEERS, INC.
2710 GATEWAY OAKS DRIVE, SUITE 190N
SACRAMENTO, CA 95833
TEL (916) 920-2020
www.cyseng.com


Rev	Description	Date	Job No:
			20097.005
			Date: 07/11/2024
			By: CYS
			Page: 210.02B

c:\Users\comachom\appdata\local\temp\AcPublish_61412\51_20097-05.dwg Time:Jul08,2024-03:44pm Login:comachom Dimscale:1 LScale:6

C:\Users\comachom\appdata\local\temp\AcPublish_95368\S1_20097-05.dwg Time: Jul 11, 2024 - 03:07pm Login: comachom DimScale: 1 LScale: 6




ATTACHMENT PLATE 1




ATTACHMENT PLATE 2

SPACER P'S, SEE PG 302
 M6x36 A2-70 DIN 933
 SS BOLT (Fu= 100 KSI)
 SUPPLIED BY ABBOTT.
 TORQUE TO 5.6 FT-LBS
 (67 IN-LBS), TYP OF 2
 PER BRACKET

VIEWED FOR CODE COMPLIANCE
 OPM-0652
 BY: William Staehlin
 DATE: 07/23/2024



DETAIL C-C




DETAIL B-B

MAX ANCHOR FORCES AT LRFD AT LEVELING LEG

	T _{max}	C _{max}	V _{max}
CASE 1 ²	1690#	2660#	551#
CASE 2 ¹	2064#	3054#	634#

1. INCLUDES OVERSTRENGTH FACTOR (Ω_b).
2. OVERSTRENGTH FACTOR (Ω_b) MUST BE APPLIED FOR ANCHORAGE TO CONC.



NOT SEOR


SHEET TITLE: MODULE: ARCHIVE II STORAGE
ATTACHMENT PLATE DETAILS


ABBOTT AUTOMATION SOLUTIONS
 ARCHIVE II, SPIRAL ELEMENT & ELEVATED TRACKS
 SUPPORTS & ATTACHMENTS


CYS STRUCTURAL ENGINEERS, INC.
 2710 GATEWAY OAKS DRIVE, SUITE 190N
 SACRAMENTO, CA 95833
 TEL (916) 920-2020
 www.cyseng.com



Rev	Description	Date	Job No:
			20097.005
			Date: 07/11/2024
			By: CYS
			Page: 210.02C

C:\Users\comachom\appdata\local\temp\AcPublish_95368\S1_20097-05.dwg Time: Jul 11, 2024 - 03:07pm Login: comachom Dimscale: 1 LScale: 6



MAX ANCHOR FORCES AT LRFD AT LEVELING LEG		
	C _{max}	V _{max}
CASE 1 ²	246#	213#
CASE 2 ¹	246#	120#

1. INCLUDES OVERSTRENGTH FACTOR (Ω_o).
2. OVERSTRENGTH FACTOR (Ω_o) MUST BE APPLIED FOR ANCHORAGE TO CONC.







REVIEWED FOR CODE COMPLIANCE
 OPM-0652
 BY: William Staehlin
 DATE: 07/23/2024
 CALIFORNIA BUILDING CODE 2022

SHEET TITLE: SPIRAL ELEMENT
 BASE PLAN & ELEVATIONS

ABBOTT AUTOMATION SOLUTIONS
 ARCHIVE II, SPIRAL ELEMENT & ELEVATED TRACKS
 SUPPORTS & ATTACHMENTS




CYS STRUCTURAL ENGINEERS, INC.
 2710 GATEWAY OAKS DRIVE, SUITE 190N
 SACRAMENTO, CA 95833
 TEL (916) 920-2020
 www.cyseng.com

Rev	Description	Date	Job No:
			20097.005
			Date: 07/11/2024
			By: CYS
			Page: 210.03



MAX ANCHOR FORCES AT LRFD		
	T _{max}	V _{max}
CASE 1	954#	551#

1. INCLUDES OVERSTRENGTH FACTOR (Ω_o).
2. OVERSTRENGTH FACTOR (Ω_o) MUST BE APPLIED FOR ANCHORAGE TO CONC.




SHEET TITLE: ELEVATED TRACK COMPONENTS: STRAIGHT SECTION - 20cm
BASE PLAN & ELEVATIONS

ABBOTT AUTOMATION SOLUTIONS
ARCHIVE II, SPIRAL ELEMENT & ELEVATED TRACKS
SUPPORTS & ATTACHMENTS


CYS STRUCTURAL ENGINEERS, INC.
2710 GATEWAY OAKS DRIVE, SUITE 190N
SACRAMENTO, CA 95833
TEL (916) 920-2020
www.cyseng.com

Rev	Description	Date	Job No:
			20097.005
			Date: 07/11/2024
			By: CYS
			Page: 210.04


c:\Users\comachom\appdata\local\temp\AcPublish_61412\S1_20097-05.dwg Time:Jul08,2024-03:44pm Login:comachom Dimscale:1 LScale:6




PLAN VIEW B-B



PLAN VIEW






SIDE ELEV



FRONT ELEV A-A

MAX ANCHOR FORCES AT LRFD		
	T _{max}	V _{max}
CASE 1	954#	551#

1. INCLUDES OVERSTRENGTH FACTOR (Ω_o).
2. OVERSTRENGTH FACTOR (Ω_o) MUST BE APPLIED FOR ANCHORAGE TO CONC.



NOT SEOR

SHEET TITLE: ELEVATED TRACK COMPONENTS: STRAIGHT SECTION - 40cm
BASE PLAN & ELEVATIONS




ABBOTT AUTOMATION SOLUTIONS
ARCHIVE II, SPIRAL ELEMENT & ELEVATED TRACKS
SUPPORTS & ATTACHMENTS

CYS STRUCTURAL ENGINEERS, INC.
2710 GATEWAY OAKS DRIVE, SUITE 190N
SACRAMENTO, CA 95833
TEL (916) 920-2020
www.cyseng.com

Rev	Description	Date	Job No:
			20097.005
			Date: 07/11/2024
			By: CYS
			Page: 210.05




C:\Users\comachom\appdata\local\temp\AcPublish_61412\S1_20097-05.dwg Time:Jul08,2024-03:44pm Login:comachom Dimscale:1 LScale:6

NOTES:
 1. 1- TRANSVERSE LATERAL BRACE MUST OCCUR EVERY 95.4" MAX. SEE LAYOUT PLAN VIEW ON PG 210.04 SIM.
 2. 1- LONGITUDINAL BRACE EVERY 95.4" MAX. SEE LAYOUT PLAN VIEW ON PG 210.04 SIM.



MAX ANCHOR FORCES AT LRFD		
	T _{max}	V _{max}
CASE 1	954#	551#

1. INCLUDES OVERSTRENGTH FACTOR (Ω_o).
2. OVERSTRENGTH FACTOR (Ω_o) MUST BE APPLIED FOR ANCHORAGE TO CONC.






SHEET TITLE: ELEVATED TRACK COMPONENTS: STRAIGHT SECTION - 80cm
 BASE PLAN & ELEVATIONS

ABBOTT AUTOMATION SOLUTIONS
 ARCHIVE II, SPIRAL ELEMENT & ELEVATED TRACKS
 SUPPORTS & ATTACHMENTS

CYS STRUCTURAL ENGINEERS, INC.
 2710 GATEWAY OAKS DRIVE, SUITE 190N
 SACRAMENTO, CA 95833
 TEL (916) 920-2020
 www.cyseng.com

Rev	Description	Date	Job No:
			20097.005
			Date: 07/11/2024
			By: CYS
			Page: 210.06


C:\Users\comachom\appdata\local\temp\AcPublish_61412\S1_20097-05.dwg Time:Jul08,2024-03:44pm Login:comachom Dimscale:1 LScale:6
 OPM-0652: Reviewed for Code Compliance by William E Staehlin



MAX ANCHOR FORCES AT LRFD		
	T _{max}	V _{max}
CASE 1 ²	954#	551#

1. INCLUDES OVERSTRENGTH FACTOR (Ω_o).

2. OVERSTRENGTH FACTOR (Ω_o) MUST BE APPLIED FOR ANCHORAGE TO CONC.



FOR TYP ELEVATED TRACK BRACKET, SEE PG 210.04

ISOMETRIC OF 90 DEG TURN SECTION



SHEET TITLE: ELEVATED TRACK COMPONENTS: 90 DEGREE TURN SECTION
BASE PLAN & ELEVATIONS




ABBOTT AUTOMATION SOLUTIONS
ARCHIVE II, SPIRAL ELEMENT & ELEVATED TRACKS
SUPPORTS & ATTACHMENTS

CYS STRUCTURAL ENGINEERS, INC.
2710 GATEWAY OAKS DRIVE, SUITE 190N
SACRAMENTO, CA 95833
TEL (916) 920-2020
www.cyseng.com

Rev	Description	Date	Job No:
			20097.005
			Date: 07/11/2024
			By: CYS
			Page: 210.07



C:\Users\comachom\appdata\local\temp\AcPublish_61412\S1_20097-05.dwg Time:Jul08,2024 -03:44pm Login:comachom Dimscale:1 LScale:6

c:\Users\comachom\appdata\local\temp\AcPublish_61412\S1_20097-05.dwg Time:Jul08,2024-03:44pm Login:comachom Dimscale:1 LScale:6



MAX ANCHOR FORCES AT LRFD			
	T _{max}	C _{max}	V _{max}
CASE 1 ²	773#	716#	446#

1. INCLUDES OVERSTRENGTH FACTOR (Ω_o).
2. OVERSTRENGTH FACTOR (Ω_o) MUST BE APPLIED FOR ANCHORAGE TO CONC.




SHEET TITLE: ELEVATED TRACK COMPONENTS: ROUNDABOUT SECTIONS
BASE PLAN & ELEVATIONS



ABBOTT AUTOMATION SOLUTIONS
ARCHIVE II, SPIRAL ELEMENT & ELEVATED TRACKS
SUPPORTS & ATTACHMENTS

CYS STRUCTURAL ENGINEERS, INC.
2710 GATEWAY OAKS DRIVE, SUITE 190N
SACRAMENTO, CA 95833
TEL (916) 920-2020
www.cyseng.com

Rev	Description	Date	Job No:
			20097.005
			Date: 07/11/2024
			By: CYS
			Page: 210.08



BASE PLAN VIEW A-A



MAX ANCHOR FORCES AT LRFD AT LEVELING LEG

	T _{max}	C _{max}	V _{max}
CASE 1 ²	294#	321#	40#
CASE 2 ¹	163#	191#	22#


1. INCLUDES OVERSTRENGTH FACTOR (Ω_o).
2. OVERSTRENGTH FACTOR (Ω_o) MUST BE APPLIED FOR ANCHORAGE TO CONC.




NOT SEOR

SHEET TITLE: FLOOR SUPPORTED TRACK: STRAIGHT SECTION - 20cm BASE PLAN & ELEVATIONS				Rev	Description	Date	Job No: 20097.005
ABBOTT AUTOMATION SOLUTIONS ARCHIVE II, SPIRAL ELEMENT & ELEVATED TRACKS SUPPORTS & ATTACHMENTS							Date: 07/11/2024
CYS STRUCTURAL ENGINEERS, INC. 2710 GATEWAY OAKS DRIVE, SUITE 190N SACRAMENTO, CA 95833							By: CYS
Abbott							Page: 210.09


c:\Users\comachom\appdata\local\temp\AcPublish_80540\S1_20097-05.dwg Time: May 13, 2024 - 10:45am Login: comachom DimScale: 1 LScale: 6




BASE PLAN VIEW A-A



FRONT ELEV




LEFT SIDE ELEV



MAX ANCHOR FORCES AT LRFD AT LEVELING LEG

	T _{max}	C _{max}	V _{max}
CASE 1 ²	778#	882#	129#
CASE 2 ¹	433#	537#	73#

1. INCLUDES OVERSTRENGTH FACTOR (Ω_b).
2. OVERSTRENGTH FACTOR (Ω_b) MUST BE APPLIED FOR ANCHORAGE TO CONC.



HAT BRACKET PER PG 310. FOR LOCATION, SEE PGS 210.01 & 210.02





NOT SEOR

<p>ABBOTT AUTOMATION SOLUTIONS ARCHIVE II, SPIRAL ELEMENT & ELEVATED TRACKS SUPPORTS & ATTACHMENTS</p>	<p>CYS STRUCTURAL ENGINEERS, INC. 2710 GATEWAY OAKS DRIVE, SUITE 190N SACRAMENTO, CA 95833 TEL (916) 920-2020 www.cyseng.com</p>	Rev	Description	Date	Job No: 20097.005
					Date: 07/11/2024
					By: CYS
					Page: 210.11

c:\Users\comachom\appdata\local\temp\AcPublish_80540\S1_20097-05.dwg Time:May 13, 2024-10:45am Login:comachom DimScale:1 LScale:6


SUPPORT FRAME

CHANNEL



TYP TRACK FRAME (EN AC-43100)
ALUM CASTING ALLOY (Fy= 38 KSI,
MIN ASSUMED)

0.071" (1.8) THK ALUM
6060-T6 EXTRUSION CHANNEL
(Fty= 35 KSI MIN, Ftu= 38 KSI
MIN), TYP AT T&B OF TRACK
SECTIONS



NOT SEOR

SHEET TITLE: FLOOR MOUNTED TRACK DETAIL
SUPPORT FRAME


ABBOTT AUTOMATION SOLUTIONS
ARCHIVE II, SPIRAL ELEMENT & ELEVATED TRACKS
SUPPORTS & ATTACHMENTS

CYS STRUCTURAL ENGINEERS, INC.
2710 GATEWAY OAKS DRIVE, SUITE 190N
SACRAMENTO, CA 95833
TEL (916) 920-2020
www.cyseng.com

Rev	Description	Date	Job No:
			20097.005
			Date: 07/11/2024
			By: CYS
			Page: 220

c:\Users\comachom\appdata\local\temp\AcPublish_80540\S1_20097-05.dwg Time: May 13, 2024 - 10:45am Login: comachom DimScale: 1 LTScale: 6

SUPPORT FRAME TO CHANNEL CONNECTION




FOR CONN BTW CHANNELS
AT T&B OF SUPPORT
FRAME, SEE DTL BLW

TYP SUPPORT FRAME PER PG 220


TYP CHANNEL PER PG 220

MATERIAL: ALUMINUM 6060-T6

SUPPORT FRAME ISOMETRIC



SUPPORT FRAME TO CHANNEL CONN



SCREW DIN 7985 M5x12-TX A2 TORQUE
TIGHTENED TO 2.5 FT-LBS (30 IN-LBS) MIN
(Fy= 65 KSI MIN, Fu= 102 KSI MIN)
WASHER DIN 9021-5,3 A2 T-SLOT NUT -
M5 STL ZINC






NOT SEOR

SHEET TITLE: FLOOR MOUNTED TRACK DETAIL SUPPORT FRAME CONNECTIONS				Rev	Description	Date	Job No: 20097.005
ABBOTT AUTOMATION SOLUTIONS ARCHIVE II, SPIRAL ELEMENT & ELEVATED TRACKS SUPPORTS & ATTACHMENTS							Date: 07/11/2024
				CYS STRUCTURAL ENGINEERS, INC. 2710 GATEWAY OAKS DRIVE, SUITE 190N TEL (916) 920-2020 SACRAMENTO, CA 95833 www.cyseng.com			
							By: CYS
							Page: 221

c:\Users\comachom\appdata\local\temp\AcPublish_95368\S1_20097-05.dwg Time: Jul 11, 2024 - 03:07pm Login: comachom Dimscale: 1 LScale: 6

c:\Users\comachom\appdata\local\temp\AcPublish_80540\51_20097-05.dwg Time:May 13, 2024 - 10:45am Login:comachom DimScale:1 LTScale:6



NOTES:

- FOR CASE 1 & CASE 2 ANCHORAGE TO FLR, SEE PGS 401-403.
- GENERAL CONTRACTOR SHALL PROVIDE & INSTALL SEISMIC BRACKET.



NOT SEOR

SHEET TITLE: SEISMIC BRACKET 1 DETAIL
LOADER MODULE

Abbott

ABBOTT AUTOMATION SOLUTIONS
ARCHIVE II, SPIRAL ELEMENT & ELEVATED TRACKS
SUPPORTS & ATTACHMENTS


CYS STRUCTURAL ENGINEERS, INC.

2710 GATEWAY OAKS DRIVE, SUITE 190N
SACRAMENTO, CA 95833


TEL (916) 920-2020
www.cyseng.com

Rev	Description	Date	Job No:
			20097.005
			Date: 07/11/2024
			By: CYS
			Page: 301

c:\Users\comachom\appdata\local\temp\AcPublish_80540\S1_20097-05.dwg Time:May 13, 2024 10:45am Login:comachom DimScale:1 LTScale:6



NOTES:
 1. FOR CASE 1 & CASE 2 ANCHORAGE TO FLR, SEE PGS 401-403.
 2. GENERAL CONTRACTOR SHALL PROVIDE & INSTALL SEISMIC BRACKET.



NOT SEOR






SHEET TITLE: SEISMIC BRACKET 1 - OPTION 2 DETAIL
 LOADER MODULE

Abbott ABBOTT AUTOMATION SOLUTIONS
 ARCHIVE II, SPIRAL ELEMENT & ELEVATED TRACKS
 SUPPORTS & ATTACHMENTS

CYS STRUCTURAL ENGINEERS, INC.
 2710 GATEWAY OAKS DRIVE, SUITE 190N TEL (916) 920-2020
 SACRAMENTO, CA 95833 www.cyseng.com

Rev	Description	Date	Job No:
			20097.005
			Date: 07/11/2024
			By: CYS
			Page: 301A

ASTM A529 GR 50 $F_y = 50$ KSI), TYP OF 2



- NOTES:**
- FOR CASE 1 & CASE 2 ANCHORAGE TO FLR, SEE PGS 401-403.
 - GENERAL CONTRACTOR SHALL PROVIDE & INSTALL SEISMIC BRACKET.




NOT SEOR


SHEET TITLE: SEISMIC BRACKET 1 - OPTION 3 DETAIL LOADER MODULE		Rev	Description	Date	Job No: 20097.005
ABBOTT AUTOMATION SOLUTIONS ARCHIVE II, SPIRAL ELEMENT & ELEVATED TRACKS SUPPORTS & ATTACHMENTS					Date: 07/11/2024
CYS STRUCTURAL ENGINEERS, INC. 2710 GATEWAY OAKS DRIVE, SUITE 190N SACRAMENTO, CA 95833					By: CYS
Abbott					Page: 301B
					TEL (916) 920-2020 www.cyseng.com

C:\Users\comachom\appdata\local\temp\AcPublish_80540\S1_20097-05.dwg Time: May 13, 2024 - 10:45am Login: comachom DimScale: 1 LTScale: 6


C:\Users\comachom\appdata\local\temp\AcPublish_61412\51_20097-05.dwg Time:Jul08,2024-03:44pm Login:comachom Dimscale:1 LTScale:6




PLAN VIEW




RIGHT BRACKET FRONT ELEVATION




TYP SPACER PLATE AT LEFT & RIGHT BRACKETS



SIDE ELEVATION







LEFT BRACKET FRONT ELEVATION



NOT SEOR

SHEET TITLE: SEISMIC BRACKET 2 DETAIL STORAGE ABBOTT AUTOMATION SOLUTIONS ARCHIVE II, SPIRAL ELEMENT & ELEVATED TRACKS SUPPORTS & ATTACHMENTS	CYS STRUCTURAL ENGINEERS, INC. 2710 GATEWAY OAKS DRIVE, SUITE 190N SACRAMENTO, CA 95833 TEL (916) 920-2020 www.cyseng.com	Rev	Description	Date	Job No: 20097.005
					Date: 07/11/2024
					By: CYS
					Page: 302

C:\Users\comachom\appdata\local\temp\AcPublish_80540\51_20097-05.dwg Time:May 13, 2024-10:45am Login:comachom DimScale:1 LTScale:6





SHEET TITLE: SEISMIC BRACKET 3 DETAIL
SPIRAL ELEMENT

Abbott
ABBOTT AUTOMATION SOLUTIONS
ARCHIVE II, SPIRAL ELEMENT & ELEVATED TRACKS
SUPPORTS & ATTACHMENTS



CYS STRUCTURAL ENGINEERS, INC.
2710 GATEWAY OAKS DRIVE, SUITE 190N
SACRAMENTO, CA 95833
TEL (916) 920-2020
www.cyseng.com

Rev	Description	Date	Job No:
			20097.005
			Date: 07/11/2024
			By: CYS
			Page: 303

C:\Users\comachom\appdata\local\temp\AcPublish_95368\S1_20097-05.dwg Time: Jul 11, 2024 - 03:07pm Login: comachom Dimscale: 1 L1Scale: 6



M6x16 BOLT W/ LOCK WASHER, INSERT INTO (E) CAPTIVE THRD NUT OF SPIRAL & TORQUE TO 5.6 FT-LBS




SHEET TITLE: SEISMIC BRACKET 4 DETAIL
SPIRAL ELEMENT

Rev	Description	Date	Job No:
			20097.005
			Date: 07/11/2024
			By: CYS
			Page: 304

Abbott
ABBOTT AUTOMATION SOLUTIONS
ARCHIVE II, SPIRAL ELEMENT & ELEVATED TRACKS
SUPPORTS & ATTACHMENTS


CYS STRUCTURAL ENGINEERS, INC.
2710 GATEWAY OAKS DRIVE, SUITE 190N
SACRAMENTO, CA 95833
TEL (916) 920-2020
www.cyseng.com

HAT BRACKET




PLAN VIEW

2- 0.625"Ø HOLES FOR SEISMIC ATTACHMENT TO FLR



ELEV



USE STL SHIM P AS REQ IN FIELD. MAX t= 0.40", IF EXCEEDED, USE 1" MAX HIGH STRENGTH GROUT

NOTES:

1. FOR CASE 1 & CASE 2 ANCHORAGE TO FLR, SEE PGS 401, 402 & 404.
2. GENERAL CONTRACTOR SHALL PROVIDE & INSTALL SEISMIC BRACKET.



NOT SEOR


SHEET TITLE: SEISMIC HAT BRACKET DETAIL
FLOOR MOUNTED TRACK

ABBOTT AUTOMATION SOLUTIONS
ARCHIVE II, SPIRAL ELEMENT & ELEVATED TRACKS
SUPPORTS & ATTACHMENTS


CYS STRUCTURAL ENGINEERS, INC.
2710 GATEWAY OAKS DRIVE, SUITE 190N
SACRAMENTO, CA 95833
TEL (916) 920-2020
www.cyseng.com

Rev	Description	Date	Job No:
			20097.005
			Date: 07/11/2024
			By: CYS
			Page: 310


c:\Users\comachom\appdata\local\temp\AcPublish_80540\51_20097-05.dwg Time:May 13, 2024 - 10:45am Login:comachom DimScale:1 LScale:6



PLAN VIEW



IN LINE ELEV



NOT SEOR

SHEET TITLE: TRACK TO COMPONENT CONNECTION

Rev	Description	Date	Job No:	20097.005
			Date:	07/11/2024
			By:	CYS
			Page:	320




ABBOTT AUTOMATION SOLUTIONS
ARCHIVE II, SPIRAL ELEMENT & ELEVATED TRACKS
SUPPORTS & ATTACHMENTS




CYS STRUCTURAL ENGINEERS, INC.
2710 GATEWAY OAKS DRIVE, SUITE 190N
SACRAMENTO, CA 95833
TEL (916) 920-2020
www.cyseng.com

HOLDER BRACKET CONNECTION

HOLDER BRACKET DETAIL







HOLDER BRACKET, TYP OF 2 PER COMPONENT & TRACK SECTION. REFER TO DTL A-A





DETAIL A-A

M5x8 A2-70 DIN 933 BOLT (Fu= 100 KSI) TORQUE TO 4.5 FT-LBS (54 IN-LBS), TYP



0.12" THK LIGHT GA STL PER EN 0088-2 3.0-1.4016+2B (Fy= 32 KSI)



NOT SEOR

SHEET TITLE: TRACK TO COMPONENT CONNECTION
HOLDER BRACKET

Rev	Description	Date	Job No:
			20097.005
			Date: 07/11/2024
			By: CYS
			Page: 321





ABBOTT AUTOMATION SOLUTIONS
ARCHIVE II, SPIRAL ELEMENT & ELEVATED TRACKS
SUPPORTS & ATTACHMENTS



CYS STRUCTURAL ENGINEERS, INC.
2710 GATEWAY OAKS DRIVE, SUITE 190N TEL (916) 920-2020
SACRAMENTO, CA 95833 www.cyseng.com


c:\Users\comachom\appdata\local\temp\AcPublish_95368\S1_20097-05.dwg Time: Jul 11, 2024 - 03:07pm Login: comachom Dimscale: 1 LScale: 6

POSITION PLATE CONNECTION





DETAIL A-A

HOLDER PLATE DETAIL



POSITION PLATE DETAIL



NOT SEOR

SHEET TITLE: TRACK TO COMPONENT CONNECTION
POSITION PLATE


ABBOTT AUTOMATION SOLUTIONS
ARCHIVE II, SPIRAL ELEMENT & ELEVATED TRACKS
SUPPORTS & ATTACHMENTS

CYS STRUCTURAL ENGINEERS, INC.
2710 GATEWAY OAKS DRIVE, SUITE 190N
SACRAMENTO, CA 95833
TEL (916) 920-2020
www.cyseng.com

Rev	Description	Date	Job No:
			20097.005
			Date: 07/11/2024
			By: CYS
			Page: 322

c:\Users\comachom\appdata\local\temp\AcPublish_61412\S1_20097-05.dwg Time:Jul08,2024-03:44pm Login:comachom Dimscale:1 LTScale:6

L:\Jobs\20097\20097 - AA System OPM\OPM 2\ACAD\STRU\SI_20097-05.dwg Time: Jul 18, 2024 - 02:49pm Login: FalkR DimScale: 1 LTScale: 6



EXTEND STRUT LENGTH TO NEXT ADJ LOW FLUTE IF AB'S ARE LESS THAN 2" FROM STRUT R SUPPORT ANCHORS

LENGTH SHALL ENGAGE TWO LOW FLUTES MIN

AB PER CASE 1, PGS 403 OR 404

AB PER CASE 1, PGS 403 OR 404

ANCHOR R PER CASE 1. COORD AB LAYOUT IN THE FIELD W/ MTL DECK ORIENTATION

SEE ANCHOR OPTIONS BLW

STRUT R, TYP. STRUT MUST ENGAGE AT LEAST TWO MTL DECK LOW FLUTES

(E) NWC OR SLWC (f'c= 3000 PSI)

STRUT R SUPPORT ANCHORS

1" MIN EITHER SIDE OF FLUTE BEND, TYP

FF TOC

A

(E) OPG WHERE OCCURS

SEE ANCHORAGE DWGS


4.5" MIN

7.5" MAX

(E) MTL DECK (20 GA MIN)

SEISMIC BRACKET 1, 2, 3 OR HAT BRACKET ABV. BRACKET 1 SHOWN

STRUT R SUPPORT ANCHORS:
 1/4" HILTI KB-TZ2 CS
 2 EA END OF R'S 6" WIDE OR WIDER,
 1 EA END OF R'S LESS THAN 6" WIDE, TYP



ANCHOR OPTIONS

BOTT OF MTL DECK (LOW FLUTES SHADED FOR CLARITY)

5/8" STRUT R. FIELD VERIFY DECK ORIENTATION FOR COORD W/ AB LAYOUT

SECTION A-A



NOT SEOR




SHEET TITLE: CASE 1 - TYPICAL STRUT DETAILS

ABBOTT AUTOMATION SOLUTIONS
 ARCHIVE II, SPIRAL ELEMENT & ELEVATED TRACKS
 SUPPORTS & ATTACHMENTS

CYS STRUCTURAL ENGINEERS, INC.
 2710 GATEWAY OAKS DRIVE, SUITE 190N
 SACRAMENTO, CA 95833
 TEL (916) 920-2020
 www.cyseng.com

Rev	Description	Date	Job No:
			20097.005
			Date: 07/11/2024
			By: CYS
			Page: 401

C:\Users\comachom\appdata\local\temp\AcPublish_61412\51_20097-05.dwg Time:Jul08,2024-03:44pm Login:comachom Dimscale:1 LScale:6



SHEET TITLE: CASE 1 - TYPICAL STRUT DETAILS

Rev	Description	Date	Job No:
			20097.005
			Date: 07/11/2024
			By: CYS
			Page: 402

ABBOTT
 ABBOTT AUTOMATION SOLUTIONS
 ARCHIVE II, SPIRAL ELEMENT & ELEVATED TRACKS
 SUPPORTS & ATTACHMENTS


CYS STRUCTURAL ENGINEERS, INC.
 2710 GATEWAY OAKS DRIVE, SUITE 190N
 SACRAMENTO, CA 95833
 TEL (916) 920-2020
 www.cyseng.com

MAX ANCHOR FORCES AT LRFD AT EA AB ⁽¹⁾		
BRACKET	Tu	Vu
1	1215#	413#
2	1119#	587#
3	0#	426#

OVERSTRENGTH FACTOR (Ω_o) MUST BE APPLIED TO V_u FOR ANCHORAGE TO CONC. FOR A BREAKDOWN, REFER TO INDIVIDUAL COMPONENTS.


MAX ANCHOR FORCES AT LRFD AT EA AB ⁽¹⁾		
BRACKET	Tu	Vu
1	718#	249#
2	1119#	587#
3	0#	240#

OVERSTRENGTH FACTOR (Ω_o) MUST BE APPLIED TO V_u FOR ANCHORAGE TO CONC. FOR A BREAKDOWN, REFER TO INDIVIDUAL COMPONENTS.



CASE 1 - SUSPENDED FLR W/ THRU-BOLTS

BRACKET #	TABLE 1	MIN		MAX		MAX GAP & JAM NUT SIZE (mm)
		MIN	MAX	MIN	MAX	
1	LOADER MODULE	2.52" (64)	2.83" (72)	2.52" (64)	2.83" (72)	8mm
2	STORAGE	4.13" (105)		4.13" (105)		N/A
3	SPIRAL ELEMENT	0.68" (17.25)	1.68" (4.25)	0.68" (17.25)	1.68" (4.25)	6mm



CASE 2 - SOG (SLAB AT OR BLW GRADE)

BRACKET #	TABLE 1	EMBED, h_{ef}		MAX GAP & JAM NUT SIZE (mm)
		MIN	MAX	
1	LOADER MODULE	2.52" (64)	2.83" (72)	8mm
2	STORAGE	4.13" (105)		N/A
3	SPIRAL ELEMENT	0.68" (17.25)	1.68" (4.25)	6mm



NOT SEOR

SHEET TITLE: CASE 1 & 2 SEISMIC BRACKETS 1,2 & 3

ABBOTT AUTOMATION SOLUTIONS
ARCHIVE II, SPIRAL ELEMENT & ELEVATED TRACKS
SUPPORTS & ATTACHMENTS

CYS STRUCTURAL ENGINEERS, INC.
2710 GATEWAY OAKS DRIVE, SUITE 190N
SACRAMENTO, CA 95833
TEL (916) 920-2020
www.cyseng.com


Rev	Description	Date	Job No:
			20097.005
			Date: 07/11/2024
			By: CYS
			Page: 403

MAX ANCHOR FORCES AT LRFD AT EA AB ⁽¹⁾	
Tu	Vu
778#	129#


OVERSTRENGTH FACTOR (Ω_o) MUST BE APPLIED TO V_u FOR ANCHORAGE TO CONC.
⁽¹⁾VALUES ARE NON-CONCURRENT. FOR A BREAKDOWN, REFER TO INDIVIDUAL COMPONENTS.

MAX ANCHOR FORCES AT LRFD AT EA AB ⁽¹⁾	
Tu	Vu
433#	73#


INCLUDES OVERSTRENGTH FACTOR (Ω_o)
⁽¹⁾VALUES ARE NON-CONCURRENT. FOR A BREAKDOWN, REFER TO INDIVIDUAL COMPONENTS.



CASE 1 - SUSPENDED FLR W/ THRU-BOLTS



CASE 2 - SOG (SLAB AT OR BLW GRADE)



NOT SEOR

SHEET TITLE: CASE 1 & 2 - SEISMIC HAT BRACKET



ABBOTT AUTOMATION SOLUTIONS
 ARCHIVE II, SPIRAL ELEMENT & ELEVATED TRACKS
 SUPPORTS & ATTACHMENTS

CYS STRUCTURAL ENGINEERS, INC.
 2710 GATEWAY OAKS DRIVE, SUITE 190N
 SACRAMENTO, CA 95833
 TEL (916) 920-2020
 www.cyseng.com

Rev	Description	Date	Job No:
			20097.005
			Date: 07/11/2024
			By: CYS
			Page: 404

MAX ANCHOR FORCES AT LRFD	
T _{max}	V _{max}
954#	551#

1. INCLUDES OVERSTRENGTH FACTOR (Ω_o).
2. OVERSTRENGTH FACTOR (Ω_o) MUST BE APPLIED FOR ANCHORAGE TO CONC.



2-1/2" HHCS BOLTS & UNISTRUT P1010 CHANNEL NUTS. FOR PROPER INSTALLATION TORQUE TWIST-OFF TYPE BOLTS UNTIL BREAKS AWAY MIN 50 FT-LBS

- NOTES:**
1. WHEN ATTACHING TO CONC FILL OVER MTL DECK, ANCHORS MUST BE INSTALLED IN LOWER FLUTE OF DECK.
 2. DTL IS TYP FOR LONGITUDINAL & TRANSVERSE BRACES.
 3. DTL MAY BE USED FOR BOTH CASE 1 & 2 LOCATIONS.




c:\Users\FalkR\AppData\Local\Temp\AcPublish_21584\SI_20097-05.dwg Time:Jul18,2024-02:56pm LogIn:FalkR DimScale:1 L1Scale:6


SHEET TITLE: ELEVATED TRACKS				Rev	Description	Date	Job No: 20097.005
SUPPORT & ATTACHMENT DETAILS TO UNDERSIDE OF MTL DECK W/ CONC FILL. BRACE STRUTS PERP TO DECK							Date: 07/11/2024
ABBOTT AUTOMATION SOLUTIONS		CYS STRUCTURAL ENGINEERS, INC.					By: CYS
ARCHIVE II, SPIRAL ELEMENT & ELEVATED TRACKS		2710 GATEWAY OAKS DRIVE, SUITE 190N					Page: 501
SUPPORTS & ATTACHMENTS		SACRAMENTO, CA 95833					
Abbott		www.cyseng.com					

MAX ANCHOR FORCES AT LRFD	
T _{max}	V _{max}
954#	551#

1. INCLUDES OVERSTRENGTH FACTOR (Ω_o).
2. OVERSTRENGTH FACTOR (Ω_o) MUST BE APPLIED FOR ANCHORAGE TO CONC.



(E) MIN 20 GA MTL DECK
W/ NWC OR SLWC
(f'_c= 3000 PSI)



2-1/2" HHCS BOLTS & UNISTRUT
P1010 CHANNEL NUTS. FOR
PROPER INSTALLATION TORQUE
TWIST-OFF TYPE BOLTS UNTIL
BREAKS AWAY MIN 50 FT-LBS

- NOTES:**
1. WHEN ATTACHING TO CONC FILL OVER MTL DECK, ANCHORS MUST BE INSTALLED IN LOWER FLUTE OF DECK.
 2. DTL IS TYP FOR LONGITUDINAL & TRANSVERSE BRACES.
 3. DTL MAY BE USED FOR BOTH CASE 1 & 2 LOCATIONS.
 4. SEE PG 501 FOR INFO NOT SHOWN.






NOT SEOR

SHEET TITLE: ELEVATED TRACKS SUPPORT & ATTACHMENT DETAILS TO UNDERSIDE OF MTL DECK W/ CONC FILL. BRACE STRUTS PARALLEL TO DECK				Rev	Description	Date	Job No: 20097.005
ABBOTT AUTOMATION SOLUTIONS ARCHIVE II, SPIRAL ELEMENT & ELEVATED TRACKS SUPPORTS & ATTACHMENTS							Date: 07/11/2024
CYS STRUCTURAL ENGINEERS, INC. 2710 GATEWAY OAKS DRIVE, SUITE 190N SACRAMENTO, CA 95833							By: CYS
Abbott							Page: 502

C:\Users\comachom\appdata\local\temp\AcPublish_61412\S1_20097-05.dwg Time:Jul08,2024-03:44pm Login:comachom Dimscale:1 LTScale:6

MAX ANCHOR FORCES AT LRFD	
T _{max}	V _{max}
954#	551#

1. INCLUDES OVERSTRENGTH FACTOR (Ω_o).
2. OVERSTRENGTH FACTOR (Ω_o) MUST BE APPLIED FOR ANCHORAGE TO CONC.



NOTES:

1. DTL IS TYP FOR LONGITUDINAL & TRANSVERSE BRACES.
2. DTL MAY BE USED FOR BOTH CASE 1 & 2 LOCATIONS.



NOT SEOR

SHEET TITLE: ELEVATED TRACKS SUPPORT & ATTACHMENT DETAILS TO UNDERSIDE OF CONCRETE FLOOR OR ROOF				Rev	Description	Date	Job No: 20097.005
ABBOTT AUTOMATION SOLUTIONS ARCHIVE II, SPIRAL ELEMENT & ELEVATED TRACKS SUPPORTS & ATTACHMENTS							Date: 07/11/2024
CYS STRUCTURAL ENGINEERS, INC. 2710 GATEWAY OAKS DRIVE, SUITE 190N SACRAMENTO, CA 95833							By: CYS
Abbott							Page: 503

C:\Users\comachom\appdata\local\temp\AcPublish_61412\S1_20097-05.dwg Time:Jul08,2024-03:44pm Login:comachom Dimscale:1 LScale:6