

DEPARTMENT OF HEALTH CARE ACCESS AND INFORMATION OFFICE OF STATEWIDE HOSPITAL PLANNING AND DEVELOPMENT

APPLICATION FOR HCAI SPECIAL SEISMIC	OFFICE USE ONLY					
CERTIFICATION PREAPPROVAL (OSP)	APPLICATION #: OSP-0418					
HCAI Special Seismic Certification Preapproval (OSP)						
Type: New X Renewal						
Manufacturer Information						
Manufacturer: RF Technologies Inc.						
Manufacturer's Technical Representative: Nasseim Bleibel						
Mailing Address: <u>3125 N 126th St,</u> , Brookfield, WI 53005						
Telephone: (262) 790-1771 Email: Quality@rft.com						
Product Information						
Product Name: Central Power Supply, 15VDC, 9A, Class II	10,					
Product Model Number(s): Part No. 9450-0555	1 Star					
Product Category: Panelboards	2					
Product Sub-Category: Power Distribution Units						
General Description: Used with Code Alert and Safe Place Solutions arim Connects multiple components to one central power source. Used with fire alarm systems and call stations.						
Mounting Description: Wall Mounted Rigid - DATE: 07/15/2025	N					
Tested Seismic Enhancements: None	0					
Applicant Information						
Applicant Company Name: EASE						
Contact Person: Jonathan Roberson						
Mailing Address: 5877 Pine Ave, Suite 210, Chino Hills, CA 91709						
Telephone: (909) 606-7622 Email: j.roberson@easeco.com						
Title: S.E.						



STATE OF CALIFORNIA – HEALTH AND HUMAN SERVICES AGENCY

"A healthier California where all receive equitable, affordable, and quality health care"

OSP-0418



DEPARTMENT OF HEALTH CARE ACCESS AND INFORMATION OFFICE OF STATEWIDE HOSPITAL PLANNING AND DEVELOPMENT

California Licensed Structural Engineer Responsible for the Engineering and Test Report(s)						
Company Name: EASE LLC						
Name: Jonathan Roberson			California License Number: S4197			
Mailing Address: 5877 Pine Ave., Suite 210, Chino Hills, CA 91709						
Telephone: (951) 295-1892 Email: jon@EASECo.com						
Certification Method						
GR-63-Core X	ICC-ES AC156		IEEE 344	IEEE 693	NEBS 3	
Other (Please Specify):						
Testing Laboratory						
Company Name: ELEMENT MA	TERIALS TECHN	OLOGY		10,		
Contact Person: Kent Erikson	L.			14		
Mailing Address: 9725 Girard A	ve Sou <mark>th, Minneap</mark>	olis MN 554	31	72		
Telephone: (952) 888-7795	R AND	Email: KLI	E@environlab.c	om m		
	O B'	/ :Mohan	nmad Karim			
	C D	ATE: 07	7/15/2025	N		
	CALIFORN					
	(Op)			4.		
		AD	DING			
			DING			



STATE OF CALIFORNIA – HEALTH AND HUMAN SERVICES AGENCY

"A healthier California where all receive equitable, affordable, and quality health care"

OSP-0418



DEPARTMENT OF HEALTH CARE ACCESS AND INFORMATION OFFICE OF STATEWIDE HOSPITAL PLANNING AND DEVELOPMENT

S	eis	mic	Par	am	eters
<u> </u>					

Desig	n Basis of Equipment or Components	(Fp/Wp) = <u>1.8</u>					
	SDS (Design spectral response acceleration at short period, g) = 2.5						
	ap (Amplification factor) =	1					
	Rp (Response modification factor) = 2.5						
	Ω_0 (System overstrength factor) = 2.0						
	lp (Importance factor) = 1.5						
	z/h (Height ratio factor) = 1						
	Natural frequencies (Hz) =	N/A					
	Overall dimensions and weight =	16" W x 6" D x 16" H; 30 lbs.					
		- OK CODE CO					
HCA	Approval (For Office Use Only) -	Approval Expires on 07/15/2037	1				
Date:	7/15/2025	S HCAI	4				
Name	e: Mohammad Karim		Title:	Supervisor, Health Facilities			
Special Seismic Certification Valid Up to: SDS (g) = 2.5				1			
Condition of Approval (if applicable): BY: Mohammad Karim							
	CALL	DATE: 07/15/2025	2000				



"A healthier California where all receive equitable, affordable, and quality health care" STATE OF CALIFORNIA – HEALTH AND HUMAN SERVICES AGENCY

OSP-0418



EQUIPMENT ANCHORAGE & SEISMIC ENGINEERING

RF Technologies

ATTACHMENT 1: TEST SPECIMEN SUMMARY

ATTACHMENT PAGE | 1 OF 1

UUT-1	Class II Centra	l Power Supply	, 15 VDC 9 A			
Manufacturer:	RF Technologies, Inc					
Identification:	Part No. 9450-0555				T	
					- A ar	4
Description:	n: Enclosure is constructed out of 16 gage (0.060") cold rolled carbon steel. ASTM A366. Internal components do not vary. Evaluation is limited to configuration tested.					
Mounting: Rigid Wall Mount using (4) 1/4-20 stainless steel thru bolts to test fixture. Alloy groups 1, 2, or 3 (300 series only), condition A, Fy = 30 ksi, Fu = 75 ksi minimum.						
Dimensions (in.)				Lowest Resonant Frequency (Hz.)		
Width	Depth	Height	Weight (lb.)	Side-Axis	Front-Axis	Vert-Axis
6	16	16	30	N/A*	N/A*	N/A*
ICC-ES AC156 Shake Table Test Parameters				5		Code: 2022 CBC
S _{DS} (G)	z/h	I _P	A _{FLX-H} (G)	A _{RIG-H} (G)	A _{FLX-V} (G)	A _{RIG-V} (G)
2.5	1	1.5	3.98	2.99	1.66	0.67
Unit satisfied AC156 N/A* - indicates that Test Report 50875-) requirements for struc the natural frequencies 1	ural integrity and man of the UUT were dom	ufacturer requiremen inated by the test tab	ts for functionality after le fixture.	r AC156 test.	

