

DEPARTMENT OF HEALTH CARE ACCESS AND INFORMATION FACILITIES DEVELOPMENT DIVISION

OFFICE USE ONLY APPLICATION FOR HCAI SPECIAL SEISMIC **CERTIFICATION PREAPPROVAL (OSP) APPLICATION #: OSP-0515 HCAI Special Seismic Certification Preapproval (OSP)** Renewal Type: New **Manufacturer Information** Manufacturer: ait-deutschland GmbH (KKT Chillers) Manufacturer's Technical Representative: Markus Zobler Mailing Address: Industriestraße 3, 95359 Kasendorf, Germany Telephone: +49 9228 99060 Email: markus.zobler@ait-deutschland.eu **Product Information** Product Name: Chillers Product Type: Chillers - CT Scanners Product Model Number: cBoxX 60 and cBoxX 70 General Description: Chiller systems for cool fluid using air cooled refrigerant. Mounting Description: See Certified Product Tables None Tested Seismic Enhancements: **Applicant Information** Applicant Company Name: W.E. Gundy & Associates, Inc. Contact Person: Travis Soppe Mailing Address: 1199 Shoreline Drive Suite 310, Boise, ID 83702

Email: tsoppe@wegai.com





Telephone: (208) 342-5989

Title: President

08/12/2022 OSP-0515 Page 1 of 8



DEPARTMENT OF HEALTH CARE ACCESS AND INFORMATION FACILITIES DEVELOPMENT DIVISION

California Licensed Structural Engineer Responsible f	or the Engineering and Test Report(s)
Company Name: W.E. GUNDY & ASOCIATES INC.	
Name: Travis Soppe	California License Number: S6115
Mailing Address: P.O. Box 9121, Boise, ID 83707	
Telephone: (208) 342-5989 Email: tsop	pe@wegai.com
Certification Method	
GR-63-Core X ICC-ES AC156	IEEE 344
Other (Please Specify):	
EOR CO	DECO
Testing Laboratory	Mp
Company Name: IABG TEST LABORATORY	
Contact Person: Dr. Steffen Roedling	7
Mailing Address: Einsteinstrasse 20, D-85521 Ottobrunn, Germ	USTS any
Telephone: +49 89 6088 2052 Email: roed	lling@iabg.de
DATE: 08/	12/2022





08/12/2022 OSP-0515 Page 2 of 8



DEPARTMENT OF HEALTH CARE ACCESS AND INFORMATION FACILITIES DEVELOPMENT DIVISION

Seismic Parameters

Design Basis of Equipment or Components (Fp/Wp) = See Attachments

SDS (Design spectral response acceleration at short period, g) = 2.0 at z/h = 1 and 2.5 at z/h = 0

ap (Amplification factor) = See attachments

Rp (Response modification factor) = See attachments

 Ω_0 (System overstrength factor) = 2.0

 I_p (Importance factor) = 1.5

z/h (Height ratio factor) = 1 and 0

Natural frequencies (Hz) = See Attachment

Overall dimensions and weight = See Attachment

HCAI Approval (For Office Use Only) Approval Expires on 08/12/2028

Date: 8/12/2022 OSP-0515

Name: Mohammad Karim Title: Supervisor, Health Facilities

OSP-0515

Special Seismic Certification Valid Up to: Sps (g) = See Above z/h = See Above

Condition of Approval (if applicable): DATE 08/12/2022





08/12/2022

KKT Chillers - AIT Deutschland GmbH SPECIAL SEISMIC CERTIFICATION CERTIFIED SYSTEM AND COMPONENTS



Manufacturer: KKT Chillers - AIT Deutschland GmbH

System: KKT Compact Chillers

System Component	KKT Chillers	Dimensions (in)			Weight	Mounting	UUT
System Component	ID Number ³	Width	Length	Height	(lb)	Mounting	UUI
cBoxX 60 Chiller	909060-00244 909060-00244z 909060-00424 909060-00424z	79.9	48.8	32.7	1,300 ²⁾	flexible floor	UUT-1
cBoxX 70 Chiller	909070-00249 909070-00249z 909070-00425 909070-00425z	79.9CC	D72.4	32.7	1,620 ²⁾	flexible floor	UUT-2
Chiller Interface Panel (CIP)	909000.0072	43.3	24.0	13.6	120	rigid wall	UUT-3
Remote Control Panel (RCP)	909 <mark>000.</mark> 0071	OSP- 11.8	12.0	4.7	11	rigid wall	UUT-4

¹⁾ All components are manufactured by AIT Deutschland GmbH unless noted otherwise. The part numbers listed uniquely identify the type of component, manufacturer, and material of construction for each sub-component within the tested units.

VIA BUILDING C

SEISMIC CERTIFICATION LIMITS										
System Component	Code	$S_{DS}(g)$	z / h	I_P	$\mathbf{a}_{\mathbf{P}}$	R_{P}	Ω_0	$\mathbf{F}_{\mathbf{P}}$ / $\mathbf{W}_{\mathbf{P}}$		
cBoxX 60 Chiller	CBC	2.0	1.0	1.50	2.5	2.5	2.0	3.60		
	2019	2.5	0	1.50	2.3			1.50		
cBoxX 70 Chiller	CBC	2.0	1.0	1.50	2.5	2.5	2.0	3.60		
CDOXA /0 CIIIIlei	2019	2.5	0					1.50		
Chiller Interface Panel	CBC	2.0	1.0	1.50	2.5	6.0	2.0	1.50		
(CIP)	2019	2.5	0	1.50	2.3	0.0	2.0	1.13		
Remote Control Panel	CBC	2.0	1.0	1.50	2.5	6.0	2.0	1.50		
(RCP)	2019	2.5	0	1.30	2.3	0.0	2.0	1.13		

08/12/2022 OSP-0515 Page 4 of 8

²⁾ Weight includes normal operating fluid used during seismic test. 2022

³⁾ The identified chillers each have two internal KKT identification numbers that are used for marketing and an additional z designation for identifying different cooling liquids (same density of tested cooling liquid). The chillers listed with the two identification numbers and additional z designations are identical in design and construction.

UNIT UNDER TEST (UUT) SUMMARY SHEET



Mounting Details: Flexible floor mounted on 4 - AMC Mecanocaucho Marinelager S/N:136024 isolation divices. Each isolator connects to the UUT with one M16 Grade 8.8 bolt and mounts to the table with 2 - M12 Grade 8.8 bolts.



Manufacturer: KKT Chillers - AIT Deutschland GmbH

Component: Compact Chiller cBoxX 60 SAP Number: 909060-00244

UUT Function: Cools liquids using an air cooled refrigerant system

UUT Description: KKT Compact Chiller with 66kW net cooling capacity. Unit is floor mounted on

vibration isolators as detailed above.

Test Location: IABG mbH, Germany Test Date: November 2016

UUT PROPERTIES

Waislet (11s)*		Dimensions (inches)	Natural Fequency (Hz)			
Weight (lb) Width Depth	Height	FB	SS	V		
1,300	79.9	48.8	32.7	4.2	3.0	9.4

Weight includes normal operating fluid.

SEISMIC TEST PARAMETERS

Building Code / Test Criteria	$S_{DS}(g)$	z / h	I_{P}	$A_{FLX-H}(g)$	$A_{RIG-H}(g)$	$A_{FLX-V}(g)$	$A_{RIG-V}(g)$
CBC 2019 / ICC-ES AC156	2.00	1.0	1.5	3.20	2.40		
	2.50	0.0	1.5			1.67	0.67

UNIT UNDER TEST (UUT) SUMMARY SHEET



Mounting Details: Flexible floor mounted on 4 - AMC Mecanocaucho Marinelager S/N:136024 isolation divices. Each isolator connects to the UUT with one M16 Grade 8.8 bolt and mounts to the table with 2 - M12 Grade 8.8 bolts.





Manufacturer: KKT Chillers - AIT Deutschland GmbH

Component: Compact Chiller cBoxX 70 SAP Number: 909070-00249

UUT Function: Cools liquids using an air cooled refrigerant system

UUT Description: KKT Compact Chiller with 79kW net cooling capacity. Unit is floor mounted on

vibration isolators as detailed above.

Test Location: IABG mbH, Germany

Test Date: November 2016

UUT PROPERTIES

W/a: ala4 (11a)*		Dimensions (inches)	Natural Fequency (Hz)			
Weight (lb)	Width	Depth	Height	FB	SS	V
1,620	79.9	72.4	32.7	4.8	2.6	8.5

Weight includes normal operating fluid.

SEISMIC TEST PARAMETERS

Building Code / Test Criteria	$S_{DS}(g)$	z / h	I_P	$A_{FLX-H}(g)$	$A_{RIG-H}(g)$	$A_{FLX-V}(g)$	$A_{RIG-V}(g)$
CBC 2019 / ICC-ES AC156	2.00	1.0	1.5	3.20	2.40		
	2.50	0.0	1.5			1.67	0.67

UNIT UNDER TEST (UUT) SUMMARY SHEET



Mounting Details: Rigid wall mounted with 3 - M8 Grade 8.8 bolts



Manufacturer: KKT Chillers - AIT Deutschland GmbH

Component: Chiller Interface Panel (CIP) SAP Number: 909000.0072

UUT Function: Serves as interface between connecting fluid lines and chiller

UUT Description: Component of KKT Chiller configurations. Contains pressure gauges, manual shut off

valve, flow meter, and thermometer.

Test Location: IABG mbH, Germany **Test Date:** April 2016

UUT PROPERTIES

Waight (1h)		Dimensions (inches)	Natural Fequency (Hz)			
Weight (lb) Width Depth	Height	FB	SS	V		
120	43.3	24	13.6	NA	NA	NA

SEISMIC TEST PARAMETERS

Building Code / Test Criteria	$S_{DS}(g)$	z / h	I_P	$A_{FLX-H}(g)$	$A_{RIG-H}(g)$	$A_{FLX-V}(g)$	$A_{RIG-V}(g)$
CBC 2019 / ICC-ES AC156	2.00	1.0	1.5	3.20	2.40		
	2.50	0.0	1.5			1.67	0.67

UNIT UNDER TEST (UUT) SUMMARY SHEET



Mounting Details: Rigid wall mounted with 4 - M8 Grade 8.8 bolts



Manufacturer: KKT Chillers - AIT Deutschland GmbH

Component: Remote Control Panel (RCP) SAP Number: 909000.0071

UUT Function: Remotely controls the KKT Compact Chillers

UUT Description: Remote control unit for KKT Compact Chiller configurations

UUT PROPERTIES

Weight (lb)		Dimensions (inches)	Natural Fequency (Hz)			
weight (10)	Weight (1b) Width Depth	Height	FB	SS	V	
11	11.8	12	4.7	NA	NA	NA

SEISMIC TEST PARAMETERS

Building Code / Test Criteria	$S_{DS}(g)$	z/h	I_{P}	$A_{FLX-H}(g)$	$A_{RIG-H}(g)$	$A_{FLX-V}(g)$	$A_{RIG-V}(g)$
CBC 2019 / ICC-ES AC156	2.00	1.0	1.5	3.20	2.40		
CBC 2019 / ICC-ES AC130	2.50	0.0	1.5			1.67	0.67