



**DEPARTMENT OF HEALTH CARE ACCESS AND INFORMATION
FACILITIES DEVELOPMENT DIVISION**

**APPLICATION FOR HCAI SPECIAL SEISMIC
CERTIFICATION PREAPPROVAL (OSP)**

OFFICE USE ONLY

APPLICATION #: OSP-0698

HCAI Special Seismic Certification Preapproval (OSP)

Type: New Renewal

Manufacturer Information

Manufacturer: Schneider Electric

Manufacturer's Technical Representative: Hao Ding

Mailing Address: 330 Weakley Ln., Smyrna, TN 37167

Telephone: (561) 848-0396

Email: hao.ding@se.com

Product Information

Product Name: UPS and Batteries

Product Type: Batteries

Product Model Number: Galaxy Lithium Ion Battery Cabinet

General Description: Li-ion Battery Cabinet with 10, 13, 14, 16, or 17 modules.

Mounting Description: Rigid, Floor Mounted

Tested Seismic Enhancements: None

DATE: 05/27/2022

Applicant Information

Applicant Company Name: Structural Integrity Associates, Inc.

Contact Person: Galen Reid

Mailing Address: 233 SW Wilson Ave Suite 101, Bend, OR 97702

Telephone: (541) 604-7225

Email: greid@structint.com

Title: Manager, TRU Compliance





**DEPARTMENT OF HEALTH CARE ACCESS AND INFORMATION
FACILITIES DEVELOPMENT DIVISION**

California Licensed Structural Engineer Responsible for the Engineering and Test Report(s)


Company Name: STRUCTURAL INTEGRITY ASSOCIATES, INC.
Name: Andrew Coughlin California License Number: S6082
Mailing Address: 5215 Hellyer Ave, Suite 101, San Jose, CA 95138-1025
Telephone: (415) 635-8461 Email: acoughlin@structint.com

Certification Method

GR-63-Core ICC-ES AC156 IEEE 344 IEEE 693 NEBS 3
 Other (Please Specify): _____

Testing Laboratory

Company Name: CHINA TELECOMMUNICATION TECHNOLOGY LABS (CTTL)
Contact Person: Lanfang Cui
Mailing Address: No. 299 Tengfei Road, Industrial Park, Lianchi District, Baoding, Hebei China
Telephone: +86 0312-6798950 Email: cuilanfang@caict.ac.cn





**DEPARTMENT OF HEALTH CARE ACCESS AND INFORMATION
FACILITIES DEVELOPMENT DIVISION**

Seismic Parameters

Design Basis of Equipment or Components (F_p/W_p) = 1.44 (SDS = 2.0); 1.13 (SDS = 2.5)

SDS (Design spectral response acceleration at short period, g) = 2.0 (z/h = 1); 2.5 (z/h = 0)

a_p (Amplification factor) = 1.0

R_p (Response modification factor) = 2.5

Ω_0 (System overstrength factor) = 2.0

I_p (Importance factor) = 1.5

z/h (Height ratio factor) = 1 and 0

Natural frequencies (Hz) = See Attachment

Overall dimensions and weight = See Attachment


HCAI Approval (For Office Use Only) - Approval Expires on 05/27/2028

Date: 5/27/2022

Name: Mohammad Karim Title: Supervisor, Health Facilities

Special Seismic Certification Valid Up to: SDS (g) = See Above z/h = See Above

Condition of Approval (if applicable): DATE: 05/27/2022



SPECIAL SEISMIC CERTIFICATION CERTIFIED SUBCOMPONENT MATRIX

2200264-CR-001-R1



Manufacturer: Schneider Electric	Table Description: Electrical Components	TABLE 2
Model Line: Galaxy Lithium Ion Battery Cabinet		

Building Code: CBC 2019 **Seismic Certification Limits:** $S_{DS} = 2.0 g$ $z/h = 1.0$ $I_p = 1.5$
 $S_{DS} = 2.5 g$ $z/h = 0.0$

Component Type	Manufacturer	Model	Description	Notes	UUT
Molded Case Circuit Breaker	Schneider Electric	LV438279	IEC Breaker		1,2,3
		LLF37060D33	UL Breaker		3
Switchgear Box	Schneider Electric	0N-87889	IEC Switchgear Box		1,2,3
		0N-2191	UL Switchgear Box		3
Battery Modules	Samsung SDI	LIBSMG95MODA	Battery Module Type A		1,2,3
		LIBSMG95MODB	Battery Module Type B		1,2,3
SMPS Box	Schneider Electric	0N-2192	SMPS Box IEC		1,2,3
		0N-1588	SMPS Box UL		3

UNIT UNDER TEST (UUT) SUMMARY SHEET

2200264-CR-001-R1



Manufacturer: Schneider Electric	UUT 1
Model Line: Galaxy Lithium Ion Battery Cabinet	
Model Number: LIBSESMG17IEC Serial Number: N/A	

Product Construction Summary:
Carbon steel cabinet

Options/Subcomponent Summary:
17 battery modules (8 Type A, 9 Type B), LV438279 Molded Case Circuit Breaker, 0N-87889 IEC Switchgear Box, 0N-2192 SMPS Box IEC

UUT Properties

Weight (lb)	Dimension (in)			Lowest Natural Frequency (Hz)		
	Depth	Width	Height	Front-Back	Side-Side	Vertical
1,069	23.2	25.6	77.6	14.8	11.9	>33.3

UUT Highest Passed Seismic Run Information

Building Code	Test Criteria	S _{DS} (g)	z/h	I _P	A _{FLX-H} (g)	A _{RIG-H} (g)	A _{FLX-V} (g)	A _{RIG-V} (g)
CBC 2019	ICC-ESAC156	2.0	1.0	1.5	3.20	2.40	1.67	0.67
		2.5	0.0					

Test Mounting Details:



Rear Seismic BKT



Front Seismic BKT

UUT was rigid base mounted to the shake table using (5) Grade 8.8 M12 Bolts in the front bracket (PN: 870-51164A), and (4) Grade 8.8 M12 Bolts in the rear bracket (PN: 870-51147).
Unit maintained structural integrity and remained functional per manufacturer requirement after shake table test.
Contents were included in testing per operating conditions.

UNIT UNDER TEST (UUT) SUMMARY SHEET



2200264-CR-001-R1

Manufacturer: Schneider Electric	UUT 2
Model Line: Galaxy Lithium Ion Battery Cabinet	
Model Number: LIBSESMG13IEC Serial Number: N/A	

Product Construction Summary:
Carbon steel cabinet

Options/Subcomponent Summary:
13 battery modules (6 Type A, 7 Type B), LV438279 Molded Case Circuit Breaker, 0N-87889 IEC Switchgear Box, 0N-2192 SMPS Box IEC

UUT Properties

Weight (lb)	Dimension (in)			Lowest Natural Frequency (Hz)		
	Depth	Width	Height	Front-Back	Side-Side	Vertical
866	23.2	25.6	77.6	14.8	11.9	>33.3

UUT Highest Passed Seismic Run Information

Building Code	Test Criteria	S _{DS} (g)	z/h	I _P	A _{FLX-H} (g)	A _{RIG-H} (g)	A _{FLX-V} (g)	A _{RIG-V} (g)
CBC 2019	ICC-ESAC156	2.0	1.0	1.5	3.20	2.40	1.67	0.67
		2.5	0.0					

Test Mounting Details:



Rear Seismic BKT



Front Seismic BKT

UUT was rigid base mounted to the shake table using (5) Grade 8.8 M12 Bolts in the front bracket (PN: 870-51164A), and (4) Grade 8.8 M12 Bolts in the rear bracket (PN: 870-51147).
Unit maintained structural integrity and remained functional per manufacturer requirement after shake table test.
Contents were included in testing per operating conditions.

UNIT UNDER TEST (UUT) SUMMARY SHEET

2200264-CR-001-R1



Manufacturer: Schneider Electric	UUT 3
Model Line: Galaxy Lithium Ion Battery Cabinet	
Model Number: LIBSESMG17IEC + LIBSESMG17UL Serial Number: N/A	


Product Construction Summary:
Carbon steel cabinet

Options/Subcomponent Summary:
17 battery modules per section (8 Type A, 9 Type B), LV438279 Molded Case Circuit Breaker, LLF37060D33 Molded Case Circuit Breaker, 0N-87889 IEC Switchgear Box, 0N-2191 UL Switchgear Box, 0N-2192 SMPS Box IEC, 0N-1588 SMPS Box UL

UUT Properties						
Weight (lb) ¹	Dimension (in)			Lowest Natural Frequency (Hz)		
	Depth	Width	Height	Front-Back	Side-Side	Vertical
2,138	23.2	51.2	77.6	12.1	12.9	>33.3

UUT Highest Passed Seismic Run Information									
Building Code	Test Criteria	S _{DS} (g)	z/h	I _P	A _{FLX-H} (g)	A _{RIG-H} (g)	A _{FLX-V} (g)	A _{RIG-V} (g)	
CBC 2019	ICC-ES AC156	2.0	1.0	1.5	3.20	2.40	1.67	0.67	
		2.5	0.0						

Test Mounting Details:



UUT was rigid base mounted to the shake table using (10) Grade 8.8 M12 Bolts in the front brackets (PN: 870-51164A), and (8) Grade 8.8 M12 Bolts in the rear brackets (PN: 870-51147)
Unit maintained structural integrity and remained functional per manufacturer requirement after shake table test.
Contents were included in testing per operating conditions.