



**DEPARTMENT OF HEALTH CARE ACCESS AND INFORMATION
FACILITIES DEVELOPMENT DIVISION**

**APPLICATION FOR HCAI SPECIAL SEISMIC
CERTIFICATION PREAPPROVAL (OSP)**

OFFICE USE ONLY

APPLICATION #: OSP-0118

HCAI Special Seismic Certification Preapproval (OSP)

Type: New Renewal

Manufacturer Information

Manufacturer: Alliance Air Products

Manufacturer's Technical Representative: Stewart Gerold

Mailing Address: 2285 Michael Faraday Drive, Suite 15, San Diego, CA 92154

Telephone: (619) 428-9688

Email: sgerold@allianceairproducts.com

Product Information

Product Name: Air Handling Units

Product Type: Fans

Product Model Number: Custom Air Handlers

General Description: Custom air handling units and associated internal componets

Mounting Description: Rigid, Floor Mounted

Tested Seismic Enhancements: None

DATE: 09/13/2022

Applicant Information

Applicant Company Name: Alliance Air Products

Contact Person: Stewart Gerold

Mailing Address: 2285 Michael Faraday Drive, Suite 15, San Diego, CA 92154

Telephone: (619) 428-9688

Email: sgerold@allianceairproducts.com

Title: Engineering Manager





**DEPARTMENT OF HEALTH CARE ACCESS AND INFORMATION
FACILITIES DEVELOPMENT DIVISION**

California Licensed Structural Engineer Responsible for the Engineering and Test Report(s)


Company Name: JUNKER ENGINEERING GROUP
Name: Dan Junker California License Number: S6178
Mailing Address: 8950 Jefferson Ave, La Mesa, CA 91941
Telephone: (619) 606-5058 Email: dan@junkereng.com

Certification Method

GR-63-Core ICC-ES AC156 IEEE 344 IEEE 693 NEBS 3
 Other (Please Specify): _____

Testing Laboratory

Company Name: CLARK TESTING LABORATORY, INC.
Contact Person: Suzanne Mazon
Mailing Address: 1801 Route 51, Jefferson Hills PA 15025
Telephone: (412) 387-1001 Email: smazon@clarktesting.com





**DEPARTMENT OF HEALTH CARE ACCESS AND INFORMATION
FACILITIES DEVELOPMENT DIVISION**

Seismic Parameters

Design Basis of Equipment or Components (F_p/W_p) = 5.63

SDS (Design spectral response acceleration at short period, g) = 2.5

a_p (Amplification factor) = 2.5

R_p (Response modification factor) = 2.0 (with internal vibration isolated components).

Ω_0 (System overstrength factor) = 2.0

I_p (Importance factor) = 1.5

z/h (Height ratio factor) = 1

Natural frequencies (Hz) = See Attachment

Overall dimensions and weight = See Attachment

HCAI Approval (For Office Use Only) - Approval Expires on 09/13/2028

Date: 9/13/2022

Name: Mohammad Karim Title: Supervisor, Health Facilities

Special Seismic Certification Valid Up to: SDS (g) = 2.5 z/h = 1

Condition of Approval (if applicable): DATE: 09/13/2022





Special Seismic Certification

Certified Components

TABLE 1

Manufacturer: Alliance Air Products, LLC

Model Line: Custom Air Handling Unit (AHU)

Table Description: AHU Cabinets

Construction Summary:

Certified unit construction shall be identical to cabinet construction of UUT's. Refer to supplemental drawings included herein for detailing requirements, materials of construction, and required seismic bracing. Units shall be constructed in accordance with Alliance Air Products typical seismic details. 2" deep 16ga Insulated panels constructed of SS, GS, or AL. 22ga solid or perforated wall liners (SS,GS,AL). 14ga to 10ga floor panels (SS,CS,AL). 1.5-2.0lb fiberglass or urethane foam insulation. 4" to 10" deep base framing (SS,GS) or 4" to 6" deep base framing (AL) perimeter channel.

** Cable cross-bracing required on all approved sections as detailed and spaced per the attached drawings

Certification Parameters:

Building Code: CBC 2022

Component Importance Factor: $I_p = 1.5$

S_{DS} at z/h = 1.0: S_{DS} = 2.5g

Options Summary:

With or without splits. With or without vestibule. Refer to supplemental drawings included herein for approved AHU cabinet layouts & configurations. Indoor or outdoor (NEMA 1 or NEMA 3R). Units within dimensions listed below certified for interior section, end section, or enclosed section.

Mounting Summary:

Rigid Floor Mount. SEOR to design anchorage.

Notes:

OSP-0118

Model Line	Model	Max Dimensions (in)			Weight (psf)	Description	UUT
		Depth	Width	Height			
Custom Air Handling Unit (AHU)	AHU Cabinets	96.0	96.0	96.0	100 Max.	Min.	
		81.0,76.0	104.0	110.0		(SS Tested)	1A,1B
		96.0	104.0	142.0		(AL Tested)	2
		134.0	104.0	142.0		(AL Tested)	3
		117.0	146.0	144.0		(GS Tested)	4A,4B
		95.0	146.0	146.0		(GS Tested)	5
		107.0	146.0	146.0		(GS Tested)	6
		111.6	146.0	144.0		(GS Tested)	7
		120.4	146.0	144.0		(GS Tested)	8
		...					
		134.0*	146.0	146.0	Max.		
* Maximum individual Module Depth							



Special Seismic Certification

Certified Sub-Components

TABLE 2.2

Manufacturer: Alliance Air Products, LLC
Model Line: Custom Air Handling Unit (AHU)
Table Description: Fans

Construction Summary: Aluminum Wheel and Carbon Steel Frame (All models).
Certification Parameters:

Note: Fan base construction on all models must be identical to that which successfully passed seismic testing. All changes made to address anomalies during testing must be implemented into certified units (must use 3/8" snubber plates).

Building Code: CBC 2022
Component Importance Factor: $I_p = 1.5$
S_{DS} at z/h = 1.0: $S_{DS} = 2.5g$

Options Summary:

5-75 Motor horsepower; 208, 230, or 460 voltage. Motors per Table 2.4

Mounting Summary:

Mounted to AHU base frame with vibration isolators.

Notes:

Sub-Component	Manufacturer	Model	Max Dimensions (in)			Weight (lb)	Description	UUT
			Depth	Width	Height			
Plenum Fans	Twin City	EPF/EPQ 122	13.8	34.8	20.0	237	Belt Drive	1A
		EPF/EPQ 150	15.8	39.0	22.5	254		
		EPF/EPQ 165	17.0	41.0	25.5	269		
		EPF/EPQ 182	19.0	45.8	26.0	312		
		EPF/EPQ 200	21.4	48.8	28.5	334		
		EPF/EPQ 222	23.0	51.8	31.5	431		
		EPF/EPQ 245	25.1	56.8	34.0	502		
		EPF/EPQ 270	27.1	63.8	37.5	541		
		EPF/EPQ 300	30.5	67.8	41.5	593		
		EPF/EPQ 330	33.8	71.8	46.0	649		
		EPF/EPQ 365	36.6	76.8	50.5	797		
		EPF/EPQ 402	39.5	85.5	56.0	954		
		EPF/EPQ 445	43.6	99.8	62.0	1120		
		EPF/EPQ 490	47.1	104.8	68.0	1405		
		EPF/EPQ 542	51.1	115.3	75.5	1599		
EPF/EPQ 600	57.6	115.3	76.0	1944		8		



Special Seismic Certification

Certified Sub-Components

TABLE 3

Manufacturer: Alliance Air Products, LLC
Model Line: Custom Air Handling Unit (AHU)
Table Description: Coils

Construction Summary: Galvanized or Stainless Steel Casing and Drain Pan; Aluminum or Copper Fins; Tube Wall Thickness: 0.016-0.049; Fin Thickness: 0.006-0.010; Fins per Inch: 4-10; 1-10 Rows; Note: Coil construction on all models must be identical to that which successfully passed seismic testing. All changes made to address anomalies during testing must be implemented into certified units (ensure coil is centered in rack, 16 GA horizontal plate to cabinet wall at mid-height).

Certification Parameters:

Options Summary: Single or stacked configuration; Hot Water or Chilled Water.

Building Code: CBC 2022
Component Importance Factor: $I_p = 1.5$
S_{DS} at z/h = 1.0: $S_{DS} = 2.5g$

Mounting Summary: Mounted within AHU. Coils shall be mounted in coil rack as tested.

Notes:

Sub-Component	Manufacturer	Model	Max Dimensions (in)			Weight (lb)	Description	UUT
			Depth	Width	Height			
Coil	Alliance Air Products, LLC	HW/CW-12Wx12H	1 Row	12.0	12.0		Min.	
		HW/CW-24Wx24H	10 Row	24.0	24.0		(Al fins, GS Casing tested)	2
		HW/CW-24Wx24H	10 Row	24.0	24.0		(Cu fins, SS Casing tested)	2
		HW/CW-130Wx60H	8 Row	130.0	60.0		(Al fins, GS Casing tested)	5
		HW/CW-130Wx60H	4 Row	130.0	60.0		(Cu fins, SS Casing tested)	5
		HW/CW-130Wx69H	10 Row	130.0	69.0		Max.	

build better together.

Document No.: 2022-114-CCS-01-00



Special Seismic Certification

Certified Sub-Components

TABLE 4

Manufacturer: Alliance Air Products, LLC
Model Line: Custom Air Handling Unit (AHU)
Table Description: Miscellaneous Components

Construction Summary: Certification Parameters:

Doors: Galvanized or Stainless Steel Exterior. Galvanized, Stainless Steel, or Aluminum Interior. 2" Injected Polyurethane Insulation.

Building Code: CBC 2022
Component Importance Factor: $I_p = 1.5$
S_{Ds} at z/h = 1.0: $S_{Ds} = 2.5g$

Options Summary:

Mounting Summary:

Mounted within AHU.

Notes:

Sub-Component	Manufacturer	Max Dimensions (in)			Weight (lb)	Description	UUT
		Depth	Width	Height			
Doors	Alliance Air Products, LLC	2.0	12.0	12.0		Min.	1B
		2.0	18.0	36.0			1B
		2.0	18.0	42.0			3
		2.0	18.0	60.0			4,A,2,5
		2.0	24.0	60.0			6,2,7
		2.0	36.0	72.0			3
		2.0	36.0	72.0			Max.
Sound Traps	Commercial Acoustics	36.0	12.0	12.0	29	Min.	1B
		48.0	48.0	48.0	438	Max.	3,3
UV Lights	Sterile Air	18.0	18.0	18.0		Min.	2
		48.0	48.0	48.0		Max.	5
Humidifier	Pure Humidifier Insty/Fast-Pac	3.0	21.0	15.0	65	Min.	2
		5.0	125.0	130.0	160	Max.	5

Special Seismic Certification

Certified Sub-Components

TABLE 9

Manufacturer: Alliance Air Products, LLC
Model Line: Custom Air Handling Unit (AHU)
Table Description: Starter Panels

Construction Summary:	Certification Parameters:
Painted galvanized carbon steel enclosure.	Building Code: CBC 2022
Options Summary:	Component Importance Factor: $I_p = 1.5$
208/230 or 460V.	S_{DS} at z/h = 1.0: S _{DS} = 2.5g
Mounting Summary:	Notes:
Mounted within AHU.	

Sub-Component	Manufacturer	Model	Max Dimensions (in)			Weight (lb)	Description		UUT
			Depth	Width	Height				
Starter Panel Enclosure	Alliance Air Products, LLC	5 HP	8.0	20.0	24.0	51	Min.		1B
		100HP	12.0	30.0	40.0	128	Max.		6
Control Transformer	Eaton	0.1 kVA					Min.		1B, 6
		2.0 kVA					Max.		1B, 6
Fuses	LittleFuse	0.5 A					Min.		1B, 6
		225.0 A					Max.		1B, 6
Disconnect	Eaton	30.0 A					Min.		1B, 6
		400.0 A					Max.		1B, 6
Contactors	Eaton	9.0 A					Min.		1B
		115.0 A					Max.		1B
	ABB	9.0 A					Min.		6
		115.0 A					Max.		6
Overload	Eaton	1.0 A					Min.		1B
		125.0 A					Max.		1B
	ABB	1.0 A					Min.		6
		125.0 A					Max.		6
Selector Switch	Eaton	M22							1B
	ABB	M2							6

Special Seismic Certification

Unit Under Test (UUT) Description

UUT **1A,1B**

Manufacturer: Alliance Air Products, LLC
Model Line: Custom Air Handling Unit (AHU)
Model number: Test Prototype - Small Cabinet Sections 1 & 2

Construction Summary: **Test Parameters:**

2" deep 16ga SS Wall Panels. 20ga SS, 20ga perforated SS, 20ga GS, 20ga perforated GS, 0.02" AL wall liners. 6" deep stainless steel base channels. 16ga SS floor lining. SS door. 3lb fiberglass insulation.

Building Code: CBC 2022
Component Importance Factor: $I_p = 1.5$
Test Criteria: AC-156

Options Summary:

Model 122 Direct Drive Aluminum Fan w/ 5 HP Baldor Motor. Model 122 Belt Drive Carbon Steel Fan w/ 5 HP Baldor Motor. Model 182 Single Fan Aluminum Stacked Fan w/ 5 HP TECO/Westinghouse Motor. 12"x12" Door. 18"x36" Door. 36" Deep Sound Trap. 22"x12" Damper. 22"x15" Louver. 4x1.5 Cell Filter Frame w/ Pre-filters. 250,000 BTU Furnace. 1.0 HP NEMA 3 VFD. 5 HP Starter Panel.


Mounting Summary:

Rigid floor mount with 5/8" grade 5 bolts at 35" o.c. at perimeter framing parallel to airflow.

Notes:

Contents were included in testing per operating conditions.

UUT Image



UUT Properties

Dimensions (in)			Weight (lb)	First Natural Frequency (Hz)		
Depth	Width	Height		F-B	S-S	Vert
81.0(A), 76.0(B)	104.0	110.0	7,845	3.0	3.3	2.8

Unit maintained structural integrity and remained operational per manufacturer requirements when subjected to the following test parameters

S_{ds} (g)	z/h	A_{FLX-H} (g)	A_{RIG-H} (g)	A_{FLX-V} (g)	A_{RIG-V} (g)
2.5	1.00	4.00	3.00	1.67	0.67

Special Seismic Certification

Unit Under Test (UUT) Description

UUT **2**

Manufacturer: Alliance Air Products, LLC
Model Line: Custom Air Handling Unit (AHU)
Model number: Test Prototype - Medium Cabinet Section 1

Construction Summary: **Test Parameters:**

2" deep 0.063" thick AL wall panels. No Liner, 0.02" AL liner, 0.02" perforated AL Liner. 6" deep AL channel base framing. 0.06" AL floor lining. 1.5lb fiberglass insulation. Injected foam insulation. AL Door. Coils mounted in coil rack.

Building Code: CBC 2022
Component Importance Factor: $I_p = 1.5$
Test Criteria: AC-156

Options Summary:

Model 182 Nine (9) Carbon Steel & Aluminum Fan Stacked Fan w/ 15 HP TECO/Westinghouse Motor. 10 Row CW-24Wx24H Copper Coil, 10 fpi, 0.016" Tube Thickness, 0.006" Fin Thickness. 10 Row CW-24Wx24H Aluminum Coil, 10 fpi, 0.049" Tube Thickness, 0.006" Fin Thickness. (1) 18" UV Light. 4.5x2 Cell Filter Frame w/ Final Filters. 21"x15" Humidifier. 24Wx60H Door. 18Wx60H Door.

Mounting Summary: **Notes:**

Rigid floor mount with 5/8" grade 5 bolts at 45" o.c. at perimeter framing parallel to airflow.

Contents were included in testing per operating conditions.

UUT Image



UUT Properties

Dimensions (in)			Weight (lb)	First Natural Frequency (Hz)		
Depth	Width	Height		F-B	S-S	Vert
96.0	104.0	142.0	5,635	7.5	7.5	12.6

Unit maintained structural integrity and remained operational per manufacturer requirements when subjected to the following test parameters

S_{ds} (g)	z/h	A_{FLX-H} (g)	A_{RIG-H} (g)	A_{FLX-V} (g)	A_{RIG-V} (g)
2.5	1.00	4.00	3.00	1.67	0.67

Special Seismic Certification

Unit Under Test (UUT) Description

UUT **3**

Manufacturer: Alliance Air Products, LLC
Model Line: Custom Air Handling Unit (AHU)
Model number: Test Prototype - Medium Cabinet Section 2

Construction Summary: **Test Parameters:**

2" deep 0.063" thick AL wall panels. 0.125" AL treadplate floor lining. No Liner, 20ga perforated GS, 20ga GS wall liners. 6" deep AL channel base framing. 1.5lb fiberglass insulation. Injected foam insulation. AL Door.

Building Code: CBC 2022
Component Importance Factor: $I_p = 1.5$
Test Criteria: AC-156

Options Summary:

18"x42" Door. 36"x72" Door. (2) 48"x48" Sound Trap. 48"x108" Damper. 50"x115" Louver. 250,000 BTU Furnace. 400,000 BTU Furnace.

Mounting Summary: **Notes:**

Rigid floor mount with 5/8" grade 5 bolts at 64" o.c. at perimeter framing parallel to airflow.

Contents were included in testing per operating conditions.

UUT Image



UUT Properties

Dimensions (in)			Weight (lb)	First Natural Frequency (Hz)		
Depth	Width	Height		F-B	S-S	Vert
134.0	104.0	142.0	4,270	4.6	15.9	13.5

Unit maintained structural integrity and remained operational per manufacturer requirements when subjected to the following test parameters

S_{ds} (g)	z/h	A_{FLX-H} (g)	A_{RIG-H} (g)	A_{FLX-V} (g)	A_{RIG-V} (g)
2.5	1.00	4.00	3.00	1.67	0.67

Special Seismic Certification

Unit Under Test (UUT) Description

UUT **4A,4B**

Manufacturer: Alliance Air Products, LLC
Model Line: Custom Air Handling Unit (AHU)
Model number: Test Prototype – Large Cabinet Sections 1 & 2

Construction Summary: **Test Parameters:**

2" deep 14ga GS wall panels. 20ga GS, 20ga perforated GS wall liners. 10ga GS floor lining. 10" deep carbon steel channel base framing. 1.5lb fiberglass insulation. GS door.

Building Code: CBC 2022
Component Importance Factor: $I_p = 1.5$
Test Criteria: AC-156

Options Summary:

GS Flat HEPA Filter Frame. 5H x 5W, 24x24x2 30% PF. 5H x 1W, 24x12x2 30% PF. 5H x 5W, 24x24x12 95% FF. 5H x 1W, 24x12x12 95% FF. 18"x60" Door. (2) 40W x 48H nearwall opening, 1 GS Damper, 1 GS Louver. (2) 40W x 48H farwall opening 1 GS Damper, 1 GS Louver.

Mounting Summary:

Rigid floor mount with 3/4" grade 5 bolts at 55" o.c. at perimeter framing parallel to airflow.

Notes:
 Contents were included in testing per operating conditions.

UUT Image



UUT Properties

Dimensions (in)			Weight (lb)	First Natural Frequency (Hz)		
Depth	Width	Height		F-B	S-S	Vert
117.0	146.0	144.0	5,270	7.0	11.9	>33.3

Unit maintained structural integrity and remained operational per manufacturer requirements when subjected to the following test parameters

S_{ds} (g)	z/h	A_{FLX-H} (g)	A_{RIG-H} (g)	A_{FLX-V} (g)	A_{RIG-V} (g)
2.5	1.00	4.00	3.00	1.67	0.67

build better together.

Document No.: 2022-114-CCS-01-00

Special Seismic Certification

Unit Under Test (UUT) Description

UUT **5**

Manufacturer: Alliance Air Products, LLC
Model Line: Custom Air Handling Unit (AHU)
Model number: Test Prototype – Large Cabinet Section 3

Construction Summary: **Test Parameters:**

2" deep 14ga GS wall panels. 20ga GS, 22ga GS wall liners, .125" carbon steel treadplate floor lining. 10" deep carbon steel channel base framing. GS Door. 1.5 lb fiberglass insulation. Coils mounted in coil rack.

Building Code: CBC 2022
Component Importance Factor: $I_p = 1.5$
Test Criteria: AC-156

Options Summary:
 4 Row HW/CW-130Wx60H Copper Coil, 8 fpi, 0.02" tube thickness, 0.01" Fin Thickness. 8 Row HW/CW-130Wx60H Aluminum Coil, 8 fpi, 0.02" tube thickness, 0.01" Fin Thickness. 16ga GS, SS drain pan. 16ga SS, GS casing. 18"x60" Door. 24"x60" Door. (5) 48" UV Lights. SS 125"x130" Humidifier.

Mounting Summary: **Notes:**

Rigid floor mount with 5/8" grade 5 bolts at 44" o.c. at perimeter framing parallel to airflow.

Contents were included in testing per operating conditions.

UUT Image



UUT Properties

Dimensions (in)			Weight (lb)	First Natural Frequency (Hz)		
Depth	Width	Height		F-B	S-S	Vert
95.0	146.0	146.0	6,850	17.4	5.9	18.2

Unit maintained structural integrity and remained operational per manufacturer requirements when subjected to the following test parameters

S_{ds} (g)	z/h	A_{FLX-H} (g)	A_{RIG-H} (g)	A_{FLX-V} (g)	A_{RIG-V} (g)
2.5	1.00	4.00	3.00	1.67	0.67

build better together.

Document No.: 2022-114-CCS-01-00

Special Seismic Certification

Unit Under Test (UUT) Description

UUT **6**

Manufacturer: Alliance Air Products, LLC
Model Line: Custom Air Handling Unit (AHU)
Model number: Test Prototype – Large Cabinet Section 4

Construction Summary: **Test Parameters:**

2" deep 16ga GS wall panels. 22ga GS, 22ga perforated GS wall liners. 16ga GS floor lining. 10" deep carbon steel channel base framing. GS Door. 1.5 lb fiberglass insulation.

Building Code: CBC 2022

Options Summary:

(2) Model 402 Direct Drive Aluminum Fans w/ 50 HP TECO/Westinghouse Motors, Carbon Steel Frame. 24"x60" Door. 100 HP Starter Panel.

Component Importance Factor: $I_p = 1.5$

Test Criteria: AC-156

Mounting Summary:

Rigid floor mount with 5/8" grade 5 bolts at 51" o.c. at perimeter framing parallel to airflow.

Notes:

Contents were included in testing per operating conditions.

UUT Image



UUT Properties

Dimensions (in)			Weight (lb)	First Natural Frequency (Hz)		
Depth	Width	Height		F-B	S-S	Vert
107.0	146.0	146.0	6,900	3.4	3.1	3.0

Unit maintained structural integrity and remained operational per manufacturer requirements when subjected to the following test parameters

S_{ds} (g)	z/h	A_{FLX-H} (g)	A_{RIG-H} (g)	A_{FLX-V} (g)	A_{RIG-V} (g)
2.5	1.00	4.00	3.00	1.67	0.67

build better together.

Document No.: 2022-114-CCS-01-00

Special Seismic Certification

Unit Under Test (UUT) Description

UUT **7**

Manufacturer: Alliance Air Products, LLC
Model Line: Custom Air Handling Unit (AHU)
Model number: Test Prototype – Large Cabinet Section 5A

Construction Summary:	Test Parameters:
2" deep 16ga GS wall panels. 20ga GS wall liners. 14ga GS floor lining. 10" deep carbon steel channel base framing. GS Door. 1.5 lb fiberglass insulation.	Building Code: CBC 2022 Component Importance Factor: $I_p = 1.5$ Test Criteria: AC-156
Options Summary:	
SS 2,250,000 BTU Furnace. 24"x60" Door. 74" Vestibule.	

Mounting Summary:	Notes:
Rigid floor mount with 5/8" grade 5 bolts at 52" o.c. at perimeter framing parallel to airflow.	Contents were included in testing per operating conditions.

UUT Image



UUT Properties

Dimensions (in)			Weight (lb)	First Natural Frequency (Hz)		
Depth	Width	Height		F-B	S-S	Vert
111.6	146.0	144.0	6,170	3.6	10.6	9.5

Unit maintained structural integrity and remained operational per manufacturer requirements when subjected to the following test parameters

S_{ds} (g)	z/h	A_{FLX-H} (g)	A_{RIG-H} (g)	A_{FLX-V} (g)	A_{RIG-V} (g)
2.5	1.00	4.00	3.00	1.67	0.67

Special Seismic Certification

Unit Under Test (UUT) Description

UUT **8**

Manufacturer: Alliance Air Products, LLC
Model Line: Custom Air Handling Unit (AHU)
Model number: Test Prototype – Large Cabinet Section 5B

Construction Summary: **Test Parameters:**

2" deep 16 ga GS wall panels. 20 ga GS wall liners. 16 ga GS floor lining. 10" deep carbon steel channel base framing. GS door. 3 lb fiberglass insulation.

Building Code: CBC 2022
Component Importance Factor: $I_p = 1.5$
Test Criteria: AC-156

Options Summary:

Model 600 direct drive aluminum fan w/ 75 HP Baldor motor, carbon steel frame. 100 HP VFD.

Mounting Summary:

Rigid floor mount with 5/8" grade 5 bolts at 57" o.c. at perimeter framing parallel to airflow.

Notes:
 Contents were included in testing per operating conditions.

UUT Image




UUT Properties


Dimensions (in)			Weight (lb)	First Natural Frequency (Hz)		
Depth	Width	Height		F-B	S-S	Vert
120.4	146.0	144.0	8,125	2.7	2.4	3.1

Unit maintained structural integrity and remained operational per manufacturer requirements when subjected to the following test parameters

S_{ds} (g)	z/h	A_{FLX-H} (g)	A_{RIG-H} (g)	A_{FLX-V} (g)	A_{RIG-V} (g)
2.5	1.00	4.00	3.00	1.67	0.67



PLAN VIEW



SIDE VIEW

- ① Access Door (See Table 4)
- ② Damper (See Table 5)
- ③ Louver (See Table 5)
- ④ Access Door (See Table 4)
- ⑤ VFD & enclosure (See Table 8)
- ⑥ Fan & motor (See Table 2)
- ⑦ Louver (See Table 5)
- ⑧ UV Lights (See Table 4)
- ⑨ Heating Coil (See Table 3)
- ⑩ Access Door (See Table 4)
- ⑪ Cooling Coil (See Table 3)
- ⑫ Access Door (See Table 4)
- ⑬ Starter Panel (See Table 9)
- ⑭ Fan & motor (See Table 2)
- ⑮ Sound Traps (See Table 4)
- ⑯ Gas Furnace (See Table 7)
- ⑰ Access Door (See Table 4)
- ⑱ Filters (See Table 6)
- ⑲ Access Door (See Table 4)
- ⑳ Access Door (See Table 4)

SECTIONS :

- CC = Cooling Coil
- PF = Plenum Fan
- ST = Sound Trap
- FF = Flat Filter
- FU = Furnace
- HC = Heating Coil
- HU = Humidifier
- MB = Mixing Box

NOTES :

1. Wall insulation 2' & 4'.
2. Cabinet Material: Galvanized Steel, Stainless Steel, Aluminum.
3. Coil rack is required for stacked coils.
4. Unit base heights 4' to 10". Base material steel, aluminum.
5. Two (2) sets of internal seismic cross bracing required @ 10'-0" o.c. max. (Typ. @ each section inlet). See Internal Cross Bracing Sheet for details.
6. Seismic cross bracing to be installed @ each side of shipping splits within AHU.
7. Shipping splits may be located at any section.

Lifting lug locations on mechanical drawing are for representation only. Actual lifting locations will vary depending engineering review.


SCHEMATIC LINE DRAWINGS FOR AIR HANDLING UNITS




2285 Michael Faraday Dr. Suite 15
 San Diego, CA 92154
 Phone (619) 428-9688
 Fax (619) 428-9689

Project Name:	OSP Inline Unit	Model:	TBD
Unit Tag:	AHU-1	Qty. :	(1) ONE EACH

PROJECT ENGINEER TSIEBER		
DESIGN ENGINEER GSALGADO		
DATE 05-01-12	SCALE N/A	DWG UNITS N/A
FILE: Bid\2012\1205\1201-001\Sub...\Mech...\MD-AHU1-1205-001.dwg		



PLAN VIEW



SIDE VIEW

- ① Access Door (See Table 4)
- ② Damper (See Table 5)
- ③ Louver (See Table 5)
- ④ Access Door (See Table 4)
- ⑤ VFD & enclosure (See Table 8)
- ⑥ Fan & motor (See Table 2)
- ⑦ Louver (See Table 5)
- ⑧ UV Lights (See Table 4)
- ⑨ Heating Coil (See Table 3)
- ⑩ Access Door (See Table 4)
- ⑪ Cooling Coil (See Table 3)
- ⑫ Access Door (See Table 4)
- ⑬ Starter Panel (See Table 9)
- ⑭ Fan & motor (See Table 2)
- ⑮ Sound Traps (See Table 4)
- ⑯ Gas Furnace (See Table 7)
- ⑰ Access Door (See Table 4)
- ⑱ Filters (See Table 6)
- ⑲ Access Door (See Table 4)
- ⑳ Access Door (See Table 4)

SECTIONS :

- CC = Cooling Coil
- PF = Plenum Fan
- ST = Sound Trap
- FF = Flat Filter
- FU = Furnace
- HC = Heating Coil
- HU = Humidifier
- MB = Mixing Box

NOTES :

1. Wall insulation 2" & 4".
2. Cabinet Material: Galvanized Steel, Stainless Steel, Aluminum.
3. Coil rack is required for stacked coils.
4. Unit base heights 4' to 10". Base material steel, aluminum.
5. Two (2) sets of internal seismic cross bracing required @ 10'-0" o.c. max. (Typ. @ each section inlet). See Internal Cross Bracing Sheet for details.
6. Seismic cross bracing to be installed @ each side of shipping splits within AHU.
7. Shipping splits may be located at any section.

Lifting lug locations on mechanical drawing are for representation only. Actual lifting locations will vary depending engineering review.

SCHEMATIC LINE DRAWINGS FOR AIR HANDLING UNITS




2285 Michael Faraday Dr. Suite 15
 San Diego, CA 92154
 Phone (619) 428-9688
 Fax (619) 428-9689

Project Name:	OSP Inline Unit w/ Splits	Model:	TBD
Unit Tag:	AHU-1	Qty. :	(1) ONE EACH

PROJECT ENGINEER TSIEBER		
DESIGN ENGINEER GSALGADO		
DATE 05-01-12	SCALE N/A	DWG UNITS N/A
FILE: Bid\2012\1205\1201-001\Sub...\Mech...\MD-AHU1-1205-001.dwg		

No.	DATE	DWN	APP
1	6/12/17	J.M.	L.P.
	SEE REVISION SHEET		



- ① Access Door (See Table 4)
- ② Damper (See Table 5)
- ③ Louver (See Table 5)
- ④ Access Door (See Table 4)
- ⑤ VFD & enclosure (See Table 8)
- ⑥ Fan & motor (See Table 2)
- ⑦ Louver (See Table 5)
- ⑧ UV Lights (See Table 4)
- ⑨ Heating Coil (See Table 3)
- ⑩ Access Door (See Table 4)
- ⑪ Cooling Coil (See Table 3)
- ⑫ Access Door (See Table 4)
- ⑬ Starter Panel (See Table 9)
- ⑭ Fan & motor (See Table 2)
- ⑮ Sound Traps (See Table 4)
- ⑯ Gas Furnace (See Table 7)
- ⑰ Access Door (See Table 4)
- ⑱ Filters (See Table 6)
- ⑲ Access Door (See Table 4)
- ⑳ Access Door (See Table 4)

SECTIONS :

- AB = Air Blender
- CC = Cooling Coil
- DF = DWDI Fan
- DX = DX Coil
- EC = Economizer
- FF = Flat Filter
- FU = Furnace
- HC = Heating Coil
- HU = Humidifier
- MB = Mixing Box

NOTES :


1. Wall insulation 2" & 4".
2. Cabinet Material: Galvanized Steel, Stainless Steel, Aluminum.
3. Coil rack is required for stacked coils.
4. Unit base heights 4' to 10'. Base material steel, aluminum.
5. Two (2) sets of internal seismic cross bracing required @ 10'-0" o.c. max. (Typ. @ each section inlet). See Internal Cross Bracing Sheet for details.
6. Seismic cross bracing to be installed @ each side of shipping splits within AHU.
7. Shipping splits may be located at any section.

Lifting lug locations on mechanical drawing are for representation only. Actual lifting locations will vary depending engineering review.

SCHEMATIC LINE DRAWING FOR AIR HANDLING UNITS

	2285 Michael Faraday Dr. Suite 15 San Diego, CA 92154 Phone (619) 428-9688 Fax (619) 428-9689	Project Name: OSP Inline Unit	Model: TBD	PROJECT ENGINEER TSIEBER	
		Unit Tag: AHU-1	Qty. : (1) ONE EACH	DESIGN ENGINEER GSALGADO	
				DATE 05-01-12	SCALE N/A
				DWG UNITS N/A	FILE: Bid\2012\1205\1201-001\Sub...\Mech...\MD-AHU1-1205-001.dwg

No.	DATE	DWN	APP
1	6/12/17	J.M.	L.P.
	SEE REVISION SHEET		



- ① Access Door (See Table 4)
- ② Damper (See Table 5)
- ③ Louver (See Table 5)
- ④ Access Door (See Table 4)
- ⑤ VFD & enclosure (See Table 8)
- ⑥ Fan & motor (See Table 2)
- ⑦ Louver (See Table 5)
- ⑧ UV Lights (See Table 4)
- ⑨ Heating Coil (See Table 3)
- ⑩ Access Door (See Table 4)
- ⑪ Cooling Coil (See Table 3)
- ⑫ Access Door (See Table 4)
- ⑬ Starter Panel (See Table 9)
- ⑭ Fan & motor (See Table 2)
- ⑮ Sound Traps (See Table 4)
- ⑯ Gas Furnace (See Table 7)
- ⑰ Access Door (See Table 4)
- ⑱ Filters (See Table 6)
- ⑲ Access Door (See Table 4)
- ⑳ Access Door (See Table 4)

SECTIONS :

- AB = Air Blender
- CC = Cooling Coil
- DF = DWDI Fan
- DX = DX Coil
- EC = Economizer
- FF = Flat Filter
- FU = Furnace
- HC = Heating Coil
- HU = Humidifier
- MB = Mixing Box


NOTES :

1. Wall insulation 2" & 4".
2. Cabinet Material: Galvanized Steel, Stainless Steel, Aluminum.
3. Coil rack is required for stacked coils.
4. Unit base heights 4' to 10'. Base material steel, aluminum.
5. Two (2) sets of internal seismic cross bracing required @ 10'-0" o.c. max. (Typ. @ each section inlet). See Internal Cross Bracing Sheet for details.
6. Seismic cross bracing to be installed @ each side of shipping splits within AHU.
7. Shipping splits may be located at any section.


Lifting lug locations on mechanical drawing are for representation only. Actual lifting locations will vary depending engineering review.

SCHEMATIC LINE DRAWING FOR AIR HANDLING UNITS

	2285 Michael Faraday Dr. Suite 15 San Diego, CA 92154 Phone (619) 428-9688 Fax (619) 428-9689	Project Name: OSP Inline Unit w /Splits	Model: TBD	PROJECT ENGINEER TSIEBER	
		Unit Tag: AHU-1	Qty. : (1) ONE EACH	DESIGN ENGINEER GSALGADO	
				DATE 05-01-12	SCALE N/A
				DWG UNITS N/A	
FILE: Bid\2012\1205\1201-001\Sub...\Mech...\MD-AHU1-1205-001.dwg					



PLAN VIEW



SIDE VIEW

- ① Access Door (See Table 4)
- ② Damper (See Table 5)
- ③ Louver (See Table 5)
- ④ Access Door (See Table 4)
- ⑤ VFD & enclosure (See Table 8)
- ⑥ Fan & motor (See Table 2)
- ⑦ Louver (See Table 5)
- ⑧ UV Lights (See Table 4)
- ⑨ Heating Coil (See Table 3)
- ⑩ Access Door (See Table 4)
- ⑪ Cooling Coil (See Table 3)
- ⑫ Access Door (See Table 4)
- ⑬ Starter Panel (See Table 9)
- ⑭ Fan & motor (See Table 2)
- ⑮ Sound Traps (See Table 4)
- ⑯ Gas Furnace (See Table 7)
- ⑰ Access Door (See Table 4)
- ⑱ Filters (See Table 6)
- ⑲ Access Door (See Table 4)
- ⑳ Access Door (See Table 4)

SECTIONS :

- CC = Cooling Coil
- PF = Plenum Fan
- ST = Sound Trap
- FF = Flat Filter
- FU = Furnace
- HC = Heating Coil
- HU = Humidifier
- MB = Mixing Box


NOTES :

1. Wall insulation 2" & 4".
2. Cabinet Material: Galvanized Steel, Stainless Steel, Aluminum.
3. Coil rack is required for stacked coils.
4. Unit base heights 4" to 10". Base material steel, aluminum.
5. Two (2) sets of internal seismic cross bracing required @ 10'-0" o.c. max. (Typ. @ each section inlet). See Internal Cross Bracing Sheet for details.
6. Seismic cross bracing to be installed @ each side of shipping splits within AHU.
7. Shipping splits may be located at any section.


Lifting lug locations on mechanical drawing are for representation only. Actual lifting locations will vary depending engineering review.

**SCHEMATIC LINE DRAWINGS
FOR AIR HANDLING UNITS**

	2285 Michael Faraday Dr. Suite 15 San Diego, CA 92154 Phone (619) 428-9688 Fax (619) 428-9689	Project Name: OSP Inline Unit Model: TBD	PROJECT ENGINEER TSIEBER DESIGN ENGINEER GSALGADO
	Unit Tag: AHU-1	Qty. : (1) ONE EACH	DATE 05-01-12 SCALE N/A DWG UNITS N/A FILE: Bid\2012\1205\1201-001\Sub...\Mech...\MD-AHU1-1205-001.dwg



PLAN VIEW



SIDE VIEW

- ① Access Door (See Table 4)
- ② Damper (See Table 5)
- ③ Louver (See Table 5)
- ④ Access Door (See Table 4)
- ⑤ VFD & enclosure (See Table 8)
- ⑥ Fan & motor (See Table 2)
- ⑦ Louver (See Table 5)
- ⑧ UV Lights (See Table 4)
- ⑨ Heating Coil (See Table 3)
- ⑩ Access Door (See Table 4)
- ⑪ Cooling Coil (See Table 3)
- ⑫ Access Door (See Table 4)
- ⑬ Starter Panel (See Table 9)
- ⑭ Fan & motor (See Table 2)
- ⑮ Sound Traps (See Table 4)
- ⑯ Gas Furnace (See Table 7)
- ⑰ Access Door (See Table 4)
- ⑱ Filters (See Table 6)
- ⑲ Access Door (See Table 4)
- ⑳ Access Door (See Table 4)

SECTIONS :

- CC = Cooling Coil
- PF = Plenum Fan
- ST = Sound Trap
- FF = Flat Filter
- FU = Furnace
- HC = Heating Coil
- HU = Humidifier
- MB = Mixing Box


NOTES :

1. Wall insulation 2' & 4'.
2. Cabinet Material: Galvanized Steel, Stainless Steel, Aluminum.
3. Coil rack is required for stacked coils.
4. Unit base heights 4' to 10". Base material steel, aluminum.
5. Two (2) sets of internal seismic cross bracing required @ 10'-0" o.c. max. (Typ. @ each section inlet). See Internal Cross Bracing Sheet for details.
6. Seismic cross bracing to be installed @ each side of shipping splits within AHU.
7. Shipping splits may be located at any section.

Lifting lug locations on mechanical drawing are for representation only. Actual lifting locations will vary depending engineering review.

SCHEMATIC LINE DRAWINGS FOR AIR HANDLING UNITS

	2285 Michael Faraday Dr. Suite 15 San Diego, CA 92154 Phone (619) 428-9688 Fax (619) 428-9689	Project Name:	OSP Inline Unit	Model:	TBD	PROJECT ENGINEER TSIEBER		
		Unit Tag:	AHU-1	Qty. :	(1) ONE EACH	DESIGN ENGINEER GSALGADO		
						DATE 05-01-12	SCALE N/A	DWG UNITS N/A
						FILE: Bid\2012\1205\1201-001\Sub...\Mech...\MD-AHU1-1205-001.dwg		



2285 Michael Faraday Dr. Suite 15
 San Diego, CA 92154
 Phone (619) 428-9688
 Fax (619) 428-9689

Project Name:	Internal Cross Bracing
Unit Tag:	Gusset

PROJECT ENGINEER TSIEBER		
DESIGN ENGINEER IMORENO		
DATE 06-06-12	SCALE NA	DWG UNITS INCHES
FILE: \\Project\1600\16003\TEMP 1109-1662\MFG\Gusset\Gusset.dwg		